MINI PILLAR


CATENARY LIGHT



LAST UPDATE: 06-11-2025



PILLAR family is a cylindrical shaped light column, bollard and wall mount luminaire with unshielded and diffused symmetrical light distribution. This creates a uniform look throughout the lighting project. The classic slim shape is the perfect choice for small to large sized spaces. Its timeless design can be used with various architectural themes and blends equally well in parks. It is utilizing multiple LED with integrated constant current driver and surge protection device. State of the art dimming options are available as well as different color temperatures and wattage options. The standard height of this luminaire is presented in this catalogue; however, it can be customized according to specific requirement. An anchorage unit is available as an accessory. Catenary mounting of luminaires is great option for tasteful illumination of outdoor spaces. Flexible arrangement of the luminaire position enables lighting designers to set the light mood to a multitude of use cases. The innovative lever clamping system utilizes a single common tool for a trouble free easy installation. All commonly used catenary wires with a diameter of 4...8mm are suitable. Wire slope of up to 20° can be easily compensated. Catenary mount luminaires are equipped with a single prewired cable of 2000mm length. Double prewired cable for looping is available upon request.



Ordering Code :

Technical Data

66 IK 10 C



Ordering Code : 1902-0-3-640-XX

Lamp: LED CCT: 4000 K CRI: CRI >80 SDCM = 3SDCM: Lamp Lumen: 1100 lm Luminaire Lumen : 860 lm Lamp Wattage: 12 W Luminaire Wattage: 14 W Efficacy: 61 lm/W Ambient Temperature : 50°C

Lumen Maintenance L80B10 >60,000 h

Controller: On-Off

Input Voltage: 220-240Vac 50/60Hz

Net Weight : - kg.

Ordering code guide

A Product Code
B Reflector
C Electrical Compo

C Electrical Component
D Lamp
F Color

IK BODY

Icon definition

MINI PILLAR

CATENARY LIGHT



LAST UPDATE: 06-11-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP66 Class II

IK Rating Protection against mechanical impact IK10 on body and IK08 on optical part.

Luminaires Body Housing High-pressure die cast aluminum alloy body and components.

Extruded aluminum S6063 alloy body with low copper content.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Self-extinguishing high impact resistant clear polycarbonate diffuser with UV stabilized additive.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on FPC.

Driver High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Terminal Block Terminal block in GFR PA6.6 for cable with cross section up to 4 sqmm. VDE approved.

Main connection provided with IP68 watertight connecting device for cable diameter 7–12mm with 2.5 sqmm section.

Pre-Wire Cable Pre-wired with 3x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.

Caution Installation work has to be carried on according to the enclosed installation manual.


Color




Graphite O2 Dark Grey O3 Aluminum Silver O4

White 06

Light Distribution






MINI PILLAR

CATENARY LIGHT



LAST UPDATE: 06-11-2025

Bug Report



Lum. Classification System (LCS)				
LCS	Zone	%Lumens	%Lamp	%Lum
FL	[0-30]	8.3	8.0	1.0
FM	[30-60]	72.0	6.5	8.4
FH	[60-80]	85.9	7.8	10.0
FVH	[80-90]	47.3	4.3	5.5
BL	[0-30]	8.3	8.0	1.0
ВМ	[30-60]	72.0	6.5	8.4
BH	[60-80]	85.9	7.8	10.0
BVH	[80-90]	47.3	4.3	5.5
UL	[90-100]	94.6	8.6	11.0
UH	[100-180]	338.1	30.7	39.3
Total		859.7	78.1	100.0
BUG Rating		BO-U3-G1		

online@unilamp.co.th

www.unilamp.co.th

MINI PILLAR

CATENARY LIGHT



LAST UPDATE: 06-11-2025

Accessories



Ordering Code: AUN-CON-0009-00 IP68 connection device, cable diameter 5-9.5mm, On-Off



Ordering Code:
AUN-CON-0010-00
IP68 connection device 3
pole, cable diameter
5-9.5mm, with distribution
block



Ordering Code: AUN-CON-0013-00 IP68 connection device, cable diameter 7-11.5mm, On-Off