# **SIRIUS**

### SIRIUS 300 - CV


CEILING MOUNT LIGHT | LINEAR LIGHT



LAST UPDATE: 14-11-2025



SIRIUS a brand new linear light family features various mounting application types including in-ground walk over, wall mounted, ceiling mounted, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.



#### **Technical Data**



Ordering Code: 4233-K-2-553-XX

Lamp: LED Beam: Asymmetric CCT: 4000 K CRI >80 CRI: SDCM: SDCM = 3Lamp Lumen: 1020 lm Luminaire Lumen : 660 lm

Lamp Wattage: 7.3 W(24Vdc) Luminaire Wattage: 7.3 W 90 lm/W Efficacy: Ambient Temperature: 50°C

Lumen Maintenance L80B10 >108,000 h

Controller: Remote Input Voltage: 24Vdc Net Weight: 1.70 kg.

Ordering code guide

XXXX-X-X-XXX-XX À

Product Code Reflector C D Electrical Component

Lamp Color

IK BODY

Icon definition

online@unilamp.co.th

www.unilamp.co.th

# **SIRIUS**

### SIRIUS 300 - CV

## CEILING MOUNT LIGHT | LINEAR LIGHT



LAST UPDATE: 14-11-2025

#### Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP67 Class III

IK Rating Protection against mechanical impact IK10 on body and IK08 on optical part.

Luminaires Body Housing Extruded aluminum S6063 alloy body with low copper content.

Coating Process Nano ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no

accumulation of dust and water.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by M2O cable gland. To be used with HO5RN-F/ HO7RN-F cable with 7-13mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver Driver is not included and has to be ordered separately.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Terminal Block Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.

Pre-Wire Cable Pre-wired with 2x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.


Equipped with anti-humidity kit.


Caution Installation work has to be carried on according to the enclosed installation manual.

Color



### Light Distribution





# **SIRIUS**

## SIRIUS 300 - CV

# CEILING MOUNT LIGHT | LINEAR LIGHT



LAST UPDATE: 14-11-2025


#### Accessories




Ordering Code: AUN-CON-0009-00 IP68 connection device, cable diameter 5-9.5mm, On-Off



Ordering Code: AUN-CON-0010-00 IP68 connection device 3 pole, cable diameter 5-9.5mm, with distribution block



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 15OW



Ordering Code: AUN-SOF-0033-00 Softening filter, LED, pre-assembly from factory



Ordering Code: AUN-GHS-0024-00 Glare shield louver, Asymmetric beam



Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W