

# TUBUS

## TUBUS ROUND – WALL DOWN


### WALL SURFACE LIGHT



LAST UPDATE: 05-06-2026



TUBUS is a family of wall up/down light operated with main voltage GU10 Retrofit LED or classic GU10 Halogen lamps. It is protected from the ingress of dust and water and can be used in both outdoor and indoor environments. TUBUS is widely used to illuminate columns and facades. The body components are made from extruded aluminium and die-cast aluminium which make it highly corrosion resistant to any extreme environment.



## Technical Data



Ordering Code :	5051-O-2-225-XX
Lamp :	LED Retrofit 220-240V
Socket :	GU10
CCT :	2700-6500 K
Lamp Wattage :	10 W
Ambient Temperature :	40°C
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	- kg.

### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition

\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(O)2 943 2420-1, +66(O)2 946 4170-1  
Fax : +66(O)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# TUBUS


## TUBUS ROUND – WALL DOWN

### WALL SURFACE LIGHT





LAST UPDATE: 05-06-2026

#### Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP65 Class II
Luminaires Body Housing	Durable high-pressure die-cast aluminum alloy for excellent mechanical performance.
Coating Process	Durable UV-resistant polyester powder coat for outdoor applications.
Diffuser	Premium tempered safety glass cover with superior mechanical strength.
Gasket	High-durability silicone gasket for long-lasting sealing performance.
External Screws	Durable stainless steel screws with anti-corrosion grease for extended lifespan.
Lamp Holder	Certified GU10 ceramic lampholder designed for high-temperature applications.
Caution	Installation must be performed as per the provided installation instructions.
Color	 Black O1 Graphite O2 Dark Gray O3 Aluminum Silver O4 White O6 Corten O8

#### Light Distribution



\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th