

MIRA

MINI MIRA ROUND – DOWN


WALL SURFACE MOUNT



LAST UPDATE: 28-02-2025



MIRA, a family of small wall light characterized by clear and clean-cut line available in round and square body. The housing is made from copper free enhanced LM6 die-cast aluminium with high corrosion resistant property. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. MIRA utilizes COB LED from industry renowned manufacturer and is available in 2700K, 3000K or 4000K, all are 3-step SDCM. The specular computer-aided-design reflector with spill light cut-off louver provides sharp light distribution on the surfaces.



Technical Data



| | |
|-----------------------|--------------------|
| Ordering Code : | 5060-F-3-904-XX |
| Lamp : | LED |
| Beam : | 104° |
| CCT : | 4000 K |
| CRI : | CRI >80 |
| SDCM : | SDCM = 3 |
| Lamp Lumen : | 1150 lm |
| Luminaire Lumen : | 860 lm |
| Lamp Wattage : | 6.5 W |
| Luminaire Wattage : | 8 W |
| Efficacy : | 107 lm/W |
| Ambient Temperature : | 40°C |
| Lumen Maintenance | L70B10 >60,000 h |
| Controller : | On-Off |
| Input Voltage : | 220-240Vac 50/60Hz |
| Net Weight : | 0.90 kg. |

Ordering code guide

XXXX-X-X-XXX-XX
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition



*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

Specification

| | |
|-------------------------|--|
| IEC Standard | IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires |
| Protection | IP66 Class I |
| IK Rating | Protection against mechanical impact IK08 on body. |
| Luminaires Body Housing | High-pressure die cast aluminum alloy body and components. |
| Coating Process | Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C. |
| Diffuser | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. |
| Reflector | High performance metallized reflector. |
| Gasket | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C. |
| External Screws | External screws are in stainless steel with protection grease. |
| Cable Entry | Cable entry protected by weather proof TPE grommet and to be used with HO5RN-F/ HO7RN-F cable with 6-13mm. diameter. |
| Led | High efficiency LED module in COB technology. Assembled on MCPCB and mounted on to heat conductive material. |
| Driver | High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard. |
| Internal Wire | Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C. |
| Terminal Block | Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved. Class1 luminaire provided with the earth connection. |
| Caution | Installation work has to be carried on according to the enclosed installation manual. |
| Color | <div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: black; margin-right: 5px;"></div> Black O1 <div style="width: 15px; height: 15px; background-color: #333; margin-right: 5px;"></div> Graphite O2 <div style="width: 15px; height: 15px; background-color: #666; margin-right: 5px;"></div> Dark Grey O3 <div style="width: 15px; height: 15px; background-color: #ccc; margin-right: 5px;"></div> Aluminum Silver O4 <div style="width: 15px; height: 15px; background-color: white; margin-right: 5px;"></div> White O6 </div> |

Light Distribution




MIRA

MINI MIRA ROUND – DOWN WALL SURFACE MOUNT



LAST UPDATE: 28-02-2025

Bug Report



Lum. Classification System [LCS]

| LCS | Zone | %Lumens | %Lamp | %Lum |
|------------|-----------|----------|-------|-------|
| FL | [0-30] | 113.8 | 11.6 | 17.2 |
| FM | [30-60] | 202.1 | 20.6 | 30.5 |
| FH | [60-80] | 14.8 | 1.5 | 2.2 |
| FVH | [80-90] | 0.1 | 0.0 | 0.0 |
| BL | [0-30] | 113.8 | 11.6 | 17.2 |
| BM | [30-60] | 202.1 | 20.6 | 30.5 |
| BH | [60-80] | 14.8 | 1.5 | 2.2 |
| BVH | [80-90] | 0.1 | 0.0 | 0.0 |
| UL | [90-100] | < 0.05 | 0.0 | 0.0 |
| UH | [100-180] | 0.3 | 0.0 | 0.0 |
| Total | | 661.9 | 67.4 | 100.0 |
| BUG Rating | | B1-U1-GO | | |

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1
Fax : +66[0]2 943 2419
online@unilamp.co.th
www.unilamp.co.th