BRONCO

BRONCO - DOWN


WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025



BRONCO is a contemporary slim luminaire family available as wall surface or ceiling mount configuration. The housing is made from extruded aluminum and enhanced LM6 die-cast aluminum which make it highly corrosion resistant to any extreme environment. BRONCO is designed and tested under high ambient thermal condition. It is protected from the ingression of dust and water and can be used for both outdoor and indoor application. The luminaire is equipped with high-power LED and is available in 2700K, 3000K, 4000K and RGBW option. Optics are utilized to direct the light in wide variety of light distributions. BRONCO is an excellent choice for a widespread range of lighting tasks in modern architectural settings such as highlighting of columns, building facades and high ceilings.



Technical Data



Ordering Code : 5205-0-5-523-XX

LED Lamp: Beam: Asymmetric CCT: 2700 K CRI >80 CRI: SDCM: SDCM = 3Lamp Lumen: 960 lm Luminaire Lumen : 830 lm Lamp Wattage: 8.1 W Luminaire Wattage: 11 W

Ambient Temperature : 50°C

Lumen Maintenance L70B10 >66,000 h

Controller : DALI

Efficacy:

Input Voltage: 220-240Vac 50/60Hz

75 lm/W

Net Weight: 1.40 kg.



Icon definition

online@unilamp.co.th

www.unilamp.co.th

BRONCO

BRONCO - DOWN

WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP65 Class I

Protection against mechanical impact IK10 on body and IK09 on optical part. IK Rating

High-pressure die cast aluminum alloy body and components. Luminaires Body Housing

Extruded aluminum S6063 alloy body with low copper content.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by weather proof grommet. To be used with HO5RN-F/ HO7RN-F cable with 6-13mm. diameter. Led

High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver High quality DALI Driver in constant current. Conform to applicable safety standards and electromagnetic compatibility. Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C. Internal Wire Terminal Block Assembled with quick connector for cable with cross section up to 2.5 sqmm. from ADELS or equivalents. VDE approved.

Class1 luminaire provided with the earth connection.

Caution Installation work has to be carried on according to the enclosed installation manual.

Color



Light Distribution

