

NOVA


NOVA SPOTLIGHT



LAST UPDATE: 28-01-2026



The NOVA projector is designed for convenient mounting on the ground or wall. Its small dimensions make it suitable for illuminating small plants and trees, as well as small signboards and architectural works. The projector is most effective when used to illuminate objects at short to medium distances. The twist-locked cover makes lamp installation easy. The projector is available in main voltage [GU10 socket].



Technical Data



Ordering Code :	5905-0-2-281-XX
Lamp :	Led Retrofit QR-CB51 12V
Socket :	GU5.3
CCT :	2700-6500 K
Lamp Wattage :	4-5 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	12Vac 50/60Hz
Net Weight :	- kg.

Ordering code guide

XXXX-X-X-XXX-XX
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(O)2 943 2420-1, +66(O)2 946 4170-1
Fax : +66(O)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

NOVA

NOVA

SPOTLIGHT





LAST UPDATE: 28-01-2026

Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires										
Protection	IP54 Class III										
Luminaires Body Housing	High-pressure Die Cast Aluminum alloy body and components.										
Coating Process	UV stablized polyester powder coat.										
Diffuser	Tempered safety glass cover										
Gasket	Durable silicone gasket										
External Screws	External screws made of stainless steel										
Lamp Holder	GU5.3 lampholder										
Pre-Wire Cable	Pre-wired with 2x1.0mm. cable										
Caution	Installation work has to be carried on according to the enclosed installation manual.										
Color	<table><tr><td></td><td>Black O1</td></tr><tr><td></td><td>Graphite O2</td></tr><tr><td></td><td>Dark Grey O3</td></tr><tr><td></td><td>Aluminum Silver O4</td></tr><tr><td></td><td>White O6</td></tr></table>		Black O1		Graphite O2		Dark Grey O3		Aluminum Silver O4		White O6
	Black O1										
	Graphite O2										
	Dark Grey O3										
	Aluminum Silver O4										
	White O6										

Light Distribution



*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

NOVA

NOVA

SPOTLIGHT

The Unilamp logo consists of a white bell icon inside a square, followed by the word "Unilamp" in a bold, white, sans-serif font, all set against a red rectangular background.

LAST UPDATE: 28-01-2026

Accessories



Ordering Code:
AUN-DRG-0115-01
Electronic Transformer,
12V, 20-60W, with IP67
GFR polymer enclosure



Ordering Code:
AUN-TRS-0033-00
Tree strap.

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1
Fax : +66[0]2 943 2419
online@unilamp.co.th
www.unilamp.co.th