

# NOVA


## NOVA CAP SPOTLIGHT



LAST UPDATE: 24-06-2025



The NOVA projector is designed for convenient mounting on the ground or wall. Its small dimensions make it suitable for illuminating small plants and trees, as well as small signboards and architectural works. The projector is most effective when used to illuminate objects at short to medium distances. The twist-locked cover makes lamp installation easy. The projector is available in two voltage options: low voltage [GU5.3 socket] and main voltage [GU10 socket].



### Technical Data



Ordering Code :	5906-O-2-281-XX
Lamp :	Led Retrofit QR-CB51 12V
Socket	GU5.3
CCT :	2700-6500 K
Lamp Wattage :	4-5 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	12Vac 50/60Hz
Net Weight :	- kg.

#### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# NOVA
















## NOVA CAP

### SPOTLIGHT





LAST UPDATE: 24-06-2025

#### Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires										
Protection	IP54 Class III										
Luminaires Body Housing	High-pressure Die Cast Aluminum alloy body and components.										
Coating Process	UV stablized polyester powder coat.										
Diffuser	Tempered safety glass cover										
Gasket	Durable silicone gasket										
External Screws	External screws made of stainless steel										
Lamp Holder	GU5.3 lampholder										
Pre-Wire Cable	Pre-wired with 2x1.0mm. cable										
Caution	Installation work has to be carried on according to the enclosed installation manual.										
Color	<table><tr><td></td><td>Black 01</td></tr><tr><td></td><td>Graphite 02</td></tr><tr><td></td><td>Dark Grey 03</td></tr><tr><td></td><td>Aluminum Silver 04</td></tr><tr><td></td><td>White 06</td></tr></table>		Black 01		Graphite 02		Dark Grey 03		Aluminum Silver 04		White 06
	Black 01										
	Graphite 02										
	Dark Grey 03										
	Aluminum Silver 04										
	White 06										

#### Light Distribution



\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# NOVA

## NOVA CAP

### SPOTLIGHT



LAST UPDATE: 24-06-2025

#### Accessories



Ordering Code:  
AUN-DRG-0115-01  
Electronic Transformer,  
12V, 20-60W, with IP67  
GFR polymer enclosure



Ordering Code:  
AUN-TRS-0033-00  
Tree strap.

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th