MINI SONIC


SPOTLIGHT



LAST UPDATE: 31-10-2025



SONIC is a huge family of spotlight/floodlight with LED, HID and retrofit light source. The family offers ground/wall mount fixing, pole clamp and wall clamp array, indirect pole and wall light. The wide ranges of accessories like glare shield unit, tree strap, earth spike and anchorage bolt kit makes SONIC customizable for most application. Available in three sizes with a choice of six colors. SONIC is fitted with COB LED with high CRI in 2700K, 3000K or 4000K color temperature with 3 SDCM. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. High specular reflectors are used in this luminaire family to achieve an outstanding light output ratio. Aiming can be done through graduated scale by tool. For ease of installation and improved thermal performance the control gear compartment is housed separately to the light engine. SONIC is an ideal choice to accentuate sculptures, walls, building facades, bushes and trees.



Technical Data



Ordering Code: 5931-0-2-221-XX Lamp: Led Retrofit QPAR51

Socket GU10

CCT: 2700-6500 K

Lamp Wattage: 4-7 W Ambient Temperature: 25°C Controller: On-Off

Input Voltage: 220-240Vac 50/60Hz

Net Weight: 1.00 kg.

Ordering code guide XXXX-X-X-XXX-XX À Product Code Reflector C D Electrical Component

IK BODY

Lamp Color

Icon definition

MINI SONIC

SPOTLIGHT



LAST UPDATE: 31-10-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP65 Class I

IK Rating Protection against mechanical impact IKO9 on body and IKO7 optical part.

Luminaires Body Housing High-pressure die cast aluminum alloy body and components.

Coating Process Nano ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Adjustable Optic Adjustable aiming unit through graduated scale.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by weather proof grommet. To be used with HO5RN-F/ HO7RN-F cable with 7–10mm. diameter.

Lamp Holder GU10 lampholder in ceramic body. VDE/ ENEC approved.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Tinned copper conductor with PTFE insulated internal wire. IMQ approved. Working temperature -40°C to +250°C.

Terminal Block Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.


Class1 luminaire provided with the earth connection.


Caution Installation work has to be carried on according to the enclosed installation manual.

Color



Light Distribution





MINI SONIC

SPOTLIGHT

LAST UPDATE: 31-10-2025



Accessories



Ordering Code: AUN-CON-0009-00 IP68 connection device, cable diameter 5-9.5mm, On-Off



Ordering Code: AUN-CON-0013-00 IP68 connection device, cable diameter 7-11.5mm, On-Off



Ordering Code:
AUN-CAB-0002-00
Cable H07RN-F 3x1sqmm,
L= 2000, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code: AUN-CLP-0004-XX Pole clamp, pole diameter 102-105mm



Ordering Code:
AUN-CAB-OO04-OO
Cable HO7RN-F 3x1sqmm,
L= 500, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code: AUN-CLP-0006-XX Pole clamp, pole diameter 60-76mm



Ordering Code: AUN-MOT-0013-XX Pole mounting arm, for 1-3 projector



Ordering Code: AUN-CLP-0008-XX Pole clamp, pole diameter 102-105mm, for wall or pole mounting arm



Ordering Code: AUN-CLP-0009-XX Pole clamp, pole diameter 60-76mm, for wall or pole mounting arm



Ordering Code: AUN-GHS-0001-XX Glare shield cap



Ordering Code: AUN-ESP-0001-00 Earth spike, GFR polymer



Ordering Code: AUN-TRS-0001-00 Tree strap, small mounting base

www.unilamp.co.th

MINI SONIC

SPOTLIGHT



LAST UPDATE: 31-10-2025





Ordering Code: Ordering Code:

ALUMINUM-POLE-FOR-SONIC-SPOTLIGHTEL-POLE-FOR-SONIC-SPOTLIGHT

Please contact Sales
Representative
Representative