MEDIUM SONIC

SPOTLIGHT




LAST UPDATE: 17-09-2025



SONIC is a huge family of spotlight/floodlight with LED, HID and retrofit light source. The family offers ground/wall mount fixing, pole clamp and wall clamp array, indirect pole and wall light. The wide ranges of accessories like glare shield unit, tree strap, earth spike and anchorage bolt kit makes SONIC customizable for most application. Available in three sizes with a choice of six colors. SONIC is fitted with COB LED with high CRI in 2700K, 3000K or 4000K color temperature with 3 SDCM. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. High specular reflectors are used in this luminaire family to achieve an outstanding light output ratio. Aiming can be done through graduated scale by tool. For ease of installation and improved thermal performance the control gear compartment is housed separately to the light engine. SONIC is an ideal choice to accentuate sculptures, walls, building facades, bushes and trees.

5933-7-3-905-XX



Technical Data

Ordering Code:

Efficacy:



Lamp: LED 48° Beam: CCT: 4000 K CRI >80 CRI: SDCM: SDCM = 3Lamp Lumen: 4920 lm Luminaire Lumen : 3420 lm Lamp Wattage: 36 W Luminaire Wattage: 41 W

Ambient Temperature : 40°C

Lumen Maintenance L70B10 >90,000 h

Controller: On-Off

Input Voltage: 220-240Vac 50/60Hz

83 lm/W

Net Weight: 2.90 kg.



Icon definition

online@unilamp.co.th

www.unilamp.co.th

MEDIUM SONIC

SPOTLIGHT

Unilamp

LAST UPDATE: 17-09-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP65 Class I

Protection against mechanical impact IKO8 on body and IKO6 optical part. IK Rating

High-pressure die cast aluminum alloy body and components. Luminaires Body Housing

Coating Process Nano ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Diffuser

Reflector High performance anodized spun aluminum reflector. Adjustable Optic Adjustable aiming unit through graduated scale.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External screws are in stainless steel with protection grease. External Screws

Cable Entry Cable entry protected by M2O cable gland. To be used with HO5RN-F/ HO7RN-F cable with 7-13mm. diameter. Led High efficiency LED module in COB technology. Assembled on MCPCB and mounted on to heat conductive material. Driver High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard. Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Tinned copper conductor with PTFE insulated internal wire. IMQ approved. Working temperature -40°C to +250°C.

Terminal Block Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.


Class1 luminaire provided with the earth connection.


Installation work has to be carried on according to the enclosed installation manual. Caution

Color



Light Distribution





MEDIUM SONIC

SPOTLIGHT

LAST UPDATE: 17-09-2025



Accessories



Ordering Code: AUN-CON-0009-00 IP68 connection device, cable diameter 5-9.5mm, On-Off



Ordering Code: AUN-CON-0013-00 IP68 connection device, cable diameter 7-11.5mm, On-Off



Ordering Code: AUN-GHS-0025-00 Glare shield ring, COB



Ordering Code:
AUN-CAB-0002-00
Cable H07RN-F 3x1sqmm,
L= 2000, with UniBlock
anti-humidity kit,
pre-assembly from factory




Ordering Code: AUN-CLP-0004-XX Pole clamp, pole diameter 102-105mm



Ordering Code:
AUN-CAB-0004-00
Cable H07RN-F 3x1sqmm,
L= 500, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code: AUN-CLP-0006-XX Pole clamp, pole diameter 60-76mm



Ordering Code: AUN-MOT-0013-XX Pole mounting arm, for 1-3 projector



Ordering Code: AUN-CLP-0008-XX Pole clamp, pole diameter 102-105mm, for wall or pole mounting arm



Ordering Code: AUN-CLP-0009-XX Pole clamp, pole diameter 60-76mm, for wall or pole mounting arm



Ordering Code: AUN-GHS-0002-XX Glare shield cap



Ordering Code: AUN-ESP-0001-00 Earth spike, GFR polymer

MEDIUM SONIC

SPOTLIGHT



LAST UPDATE: 17-09-2025



Ordering Code: AUN-TRS-0001-00 Tree strap, small mounting base



Ordering Code:

ALUMINUM-POLE-FOR-SONIC-SPOTLISHTEEL-POLE-FOR-SONIC-SPOTLIGHT
Please contact Sales

Representative

Ordering Code:

Please contact Sales

Representative



online@unilamp.co.th

www.unilamp.co.th