KUBIK


SPOTLIGHT



LAST UPDATE: 24-06-2025



KUBIK is a robust cube-shaped/rectangular-shaped spotlight/floodlight with LED and HID light source. The family offers ground/wall mount fixing, pole clamp and wall clamp array, indirect pole and indirect wall light. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. High-efficiency lenses and reflectors are used in this luminaire family. Aiming can be done through graduated scale by the tool. KUBIK is suitable to light up the object from short to medium distance for example bushes, plants, sculptures, flags, signboards, columns, building facets, playgrounds, open spaces etc. Full list of accessories is available as standard option.



Technical Data



Ordering Code: 5942-0-2-262-XX Lamp: Led Retrofit PAR30

Socket E27

CCT: 2700-6500 K Lamp Wattage: 10-15 W Ambient Temperature: 25°C Controller: On-Off

Input Voltage: 220-240Vac 50/60Hz

Net Weight: 4.60 kg.

Ordering code guide

XXXX-X-X-XXX-XX

Product Code

Reflector C D E Electrical Component

Lamp Color

IK BODY

Icon definition

online@unilamp.co.th www.unilamp.co.th



SPOTLIGHT



LAST UPDATE: 24-06-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP66 Class II

IK Rating Protection against mechanical impact IKO9 on body and optical part.

Luminaires Body Housing High-pressure die cast aluminum alloy body and components.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no

accumulation of dust and water.

Adjustable Optic Adjustable aiming unit through graduated scale.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by M2O cable gland. To be used with HO5RN-F/ HO7RN-F cable with 7-13mm. diameter.

Lamp Holder E27 lampholder in ceramic body. VDE/ ENEC approved.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Terminal Block Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.

Caution Installation work has to be carried on according to the enclosed installation manual.

Color




Black O1 Graphite O2 Dark Grey O3 Aluminum Silver O4 White O6


Whit Silve Silve

2 TONE COLOR

White-Dark Grey 21 Silver-Dark Grey 22 Silver-Graphite 23

Light Distribution





KUBIK

SPOTLIGHT



LAST UPDATE: 24-06-2025

Accessories



Ordering Code:
AUN-CAB-0001-00
Cable H07RN-F 2x1sqmm,
L= 2000, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code: AUN-CLP-0005-XX Pole clamp, pole diameter 102-105mm



Ordering Code: AUN-MOT-0005-XX Wall array, for 2 projector



Ordering Code: AUN-MOT-0006-XX Wall array, for 4 projector



Ordering Code: AUN-MOT-0007-XX Wall array, for 6 projector



Ordering Code: AUN-POL-OO25-XX Pole array for 2 projector



Ordering Code: AUN-POL-0026-XX Pole array for 4 projector



Ordering Code: AUN-POL-0027-XX Pole array for 6 projector



Ordering Code:
AUN-CAB-OOO5-OO
Cable HO5RN-F 2x1sqmm,
L= 500, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code: AUN-GHS-0007-XX Glare shield cap



Ordering Code: AUN-GSH-0036-01 Barn door shield



Ordering Code: ALUMINUM-POLE-FOR-KUBIK-POLE Please contact Sales Representative

KUBIK

SPOTLIGHT



LAST UPDATE: 24-06-2025



Ordering Code: STEEL-POLE-FOR-KUBIK-POLE Please contact Sales Representative