

# KUBIK


## KUBIK – GROUND MOUNT SPOTLIGHT



LAST UPDATE: 08-01-2024



KUBIK is a robust cube-shaped/rectangular-shaped spotlight/floodlight with LED and HID light source. The family offers ground/wall mount fixing, pole clamp and wall clamp array, indirect pole and indirect wall light. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. High-efficiency lenses and reflectors are used in this luminaire family. Aiming can be done through graduated scale by the tool. KUBIK is suitable to light up the object from short to medium distance for example bushes, plants, sculptures, flags, signboards, columns, building facets, playgrounds, open spaces etc. Full list of accessories is available as standard option.



### Technical Data



Ordering Code :	5942-0-2-262-XX
Lamp :	PAR30
Socket :	E27
Beam :	10°,30°
CCT :	2900 K
Lamp Lumen :	1100 lm
Luminaire Lumen :	1100 lm
Lamp Wattage :	75 W
Luminaire Wattage :	75 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	4.60 kg.

#### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

A Product Code  
B Reflector  
C Electrical Component  
D Lamp  
E Color



Icon definition



\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

### Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP66 Class II
IK Rating	Protection against mechanical impact IK09 on body and optical part.
Luminaires Body Housing	High-pressure Die Cast Aluminium alloy body and components.
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no accumulation of dust and water.
Adjustable Optic	Adjustable aiming unit through graduated scale.
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.
External Screws	External screws are in stainless steel with protection grease.
Cable Entry	Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.
Lamp Holder	E27 lampholder in ceramic body. VDE/ ENEC approved.
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Terminal Block	Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.
Caution	Installation work has to be carried on according to the enclosed installation manual.
Color	<div> <div> <div></div>Black 01 <div></div>Graphite 02 <div></div>Dark Grey 03 <div></div>Aluminium Silver 04 <div></div>White 06 <div></div>Wooden Brown 07 </div> <div> <b>2 TONE COLOR</b> <div> <div></div>White-Dark Grey 21 <div></div>Silver-Dark Grey 22 <div></div>Silver-Graphite 23 </div> </div> </div>

### Light Distribution



#### Accessories



Ordering Code:

AUN-CAB-0001-00


Cable H07RN-F 2x1sqmm  
length 2000 mm with  
anti-humidity kit.  
[pre-assembled from  
factory]



Ordering Code:

AUN-CLP-0005-XX


Pole\_Clamp\_Diameter\_102-105mm



Ordering Code:

AUN-MOT-0005-XX


Wall\_Array\_for\_2\_Spotlights



Ordering Code:

AUN-MOT-0006-XX

Wall\_Array\_for\_4\_Spotlights



Ordering Code:

AUN-MOT-0007-XX

Wall\_Array\_for\_6\_Spotlights



Ordering Code:

AUN-POL-0025-XX


Pole\_Array\_for\_2\_Spotlights



Ordering Code:

AUN-POL-0026-XX

Pole\_Array\_for\_4\_Spotlights



Ordering Code:

AUN-POL-0027-XX


Pole\_Array\_for\_6\_Spotlights



Ordering Code:

AUN-CAB-0005-00


Cable H05RN-F 2x1sqmm  
length 500mm. with  
anti-humidity  
kit.[pre-assembled from  
factory]



Ordering Code:

AUN-GHS-0007-XX

Glare Shield Cap



Ordering Code:

AUN-GSH-0036-01

Barn Doors



Ordering Code:

ALUMINIUM-POLE-FOR-KUBIK-POLE

Please contact Sales  
Representative

# KUBIK

KUBIK – GROUND MOUNT

SPOTLIGHT



LAST UPDATE: 08-01-2024



Ordering Code:

STEEL-POLE-FOR-KUBIK-POLE

Please contact Sales

Representative

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th