

KUBIK

KUBIK PROJECTOR



LAST UPDATE: 28-02-2025



KUBIK is a robust cube-shaped/rectangular-shaped spotlight/floodlight with LED and HID light source. The family offers ground/wall mount fixing, pole clamp and wall clamp array, indirect pole and indirect wall light. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. High-efficiency lenses and reflectors are used in this luminaire family. Aiming can be done through graduated scale by the tool. KUBIK is suitable to light up the object from short to medium distance for example bushes, plants, sculptures, flags, signboards, columns, building facets, playgrounds, open spaces etc. Full list of accessories is available as standard option.



Technical Data



Ordering Code :	5942-0-2-262-XX
Lamp :	PAR30
Socket :	E27
Beam :	10°, 30°
CCT :	2900 K
Lamp Lumen :	1100 lm
Luminaire Lumen :	1100 lm
Lamp Wattage :	75 W
Luminaire Wattage :	75 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	4.60 kg.

Ordering code guide

XXXX-X-X-XXX-XX

A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



























Icon definition



*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires																				
Protection	IP66 Class II																				
IK Rating	Protection against mechanical impact IK09 on body and optical part.																				
Luminaires Body Housing	High-pressure die cast aluminum alloy body and components.																				
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.																				
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no accumulation of dust and water.																				
Adjustable Optic	Adjustable aiming unit through graduated scale.																				
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.																				
External Screws	External screws are in stainless steel with protection grease.																				
Cable Entry	Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.																				
Lamp Holder	E27 lampholder in ceramic body. VDE/ ENEC approved.																				
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.																				
Terminal Block	Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.																				
Caution	Installation work has to be carried on according to the enclosed installation manual.																				
Color	<table border="0"> <tr> <td></td> <td>Black 01</td> <td></td> <td>White-Dark Grey 21</td> </tr> <tr> <td></td> <td>Graphite 02</td> <td></td> <td>Silver-Dark Grey 22</td> </tr> <tr> <td></td> <td>Dark Grey 03</td> <td></td> <td>Silver-Graphite 23</td> </tr> <tr> <td></td> <td>Aluminium Silver 04</td> <td></td> <td></td> </tr> <tr> <td></td> <td>White 06</td> <td></td> <td></td> </tr> </table>		Black 01		White-Dark Grey 21		Graphite 02		Silver-Dark Grey 22		Dark Grey 03		Silver-Graphite 23		Aluminium Silver 04				White 06		
	Black 01		White-Dark Grey 21																		
	Graphite 02		Silver-Dark Grey 22																		
	Dark Grey 03		Silver-Graphite 23																		
	Aluminium Silver 04																				
	White 06																				

Light Distribution




Accessories




Ordering Code:
AUN-CAB-0001-00
Cable H07RN-F 2x1sqmm,
L= 2000, with UniBlock
anti-humidity kit,
pre-assembly from factory




Ordering Code:
AUN-CLP-0005-XX
Pole clamp, pole diameter
102-105mm




Ordering Code:
AUN-MOT-0005-XX
Wall array, for 2 projector




Ordering Code:
AUN-MOT-0006-XX
Wall array, for 4 projector




Ordering Code:
AUN-MOT-0007-XX
Wall array, for 6 projector



Ordering Code:
AUN-POL-0025-XX
Pole array for 2 projector




Ordering Code:
AUN-POL-0026-XX
Pole array for 4 projector




Ordering Code:
AUN-POL-0027-XX
Pole array for 6 projector



Ordering Code:
AUN-CAB-0005-00
Cable H05RN-F 2x1sqmm,
L= 500, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code:
AUN-GHS-0007-XX
Glare shield cap



Ordering Code:
AUN-GSH-0036-01
Barn door shield



Ordering Code:
ALUMINUM-POLE-FOR-KUBIK-POLE
Please contact Sales
Representative

KUBIK

KUBIK

PROJECTOR

 **Unilamp**

LAST UPDATE: 28-02-2025



Ordering Code:

STEEL-POLE-FOR-KUBIK-POLE

Please contact Sales

Representative

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1
Fax : +66[0]2 943 2419
online@unilamp.co.th
www.unilamp.co.th