

KUBIK


KUBIK – GROUND MOUNT PROJECTOR



LAST UPDATE: 15-05-2024



KUBIK is a robust cube-shaped/rectangular-shaped spotlight/floodlight with LED and HID light source. The family offers ground/wall mount fixing, pole clamp and wall clamp array, indirect pole and indirect wall light. The front glass cover is flush to the luminaire housing thus dust and water are not accumulated. High-efficiency lenses and reflectors are used in this luminaire family. Aiming can be done through graduated scale by the tool. KUBIK is suitable to light up the object from short to medium distance for example bushes, plants, sculptures, flags, signboards, columns, building facets, playgrounds, open spaces etc. Full list of accessories is available as standard option.



Technical Data



Ordering Code :	5942-6-3-781-XX
Lamp :	HIT-CE
Socket :	G12
Beam :	28°
CCT :	3000-4200 K
Lamp Lumen :	6600 lm
Luminaire Lumen :	6600 lm
Lamp Wattage :	70 W
Luminaire Wattage :	70 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	4.90 kg.

Ordering code guide

XXXX-X-X-XXX-XX

A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color





Icon definition



*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires	
Protection	IP66 Class II	
IK Rating	Protection against mechanical impact IK09 on body and optical part.	
Luminaires Body Housing	High-pressure die cast aluminum alloy body and components.	
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.	
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no accumulation of dust and water.	
Reflector	High performance anodized spun aluminium reflector.	
Adjustable Optic	Adjustable aiming unit through graduated scale.	
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.	
External Screws	External screws are in stainless steel with protection grease.	
Cable Entry	Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.	
Lamp Holder	G12 lampholder in ceramic body. VDE/ ENEC approved.	
Ballast	Electronic ballast for HID lamp. ENEC approved.	
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C. HID control gear wired with double insulated silicone cable and compatible to be operated under ignition voltage up to 5KV.	
Terminal Block	Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.	
Caution	Installation work has to be carried on according to the enclosed installation manual.	
Color		2 TONE COLOR 

Light Distribution




Accessories



Ordering Code:
AUN-CAB-0001-00
Cable H07RN-F 2x1sqmm,
L= 2000, with UniBlock
anti-humidity kit,
pre-assembly from factory




Ordering Code:
AUN-CLP-0005-XX
Pole clamp, pole diameter
102-105mm




Ordering Code:
AUN-MOT-0005-XX
Wall array, for 2 projector




Ordering Code:
AUN-MOT-0006-XX
Wall array, for 4 projector




Ordering Code:
AUN-MOT-0007-XX
Wall array, for 6 projector



Ordering Code:
AUN-POL-0025-XX
Pole array for 2 projector



Ordering Code:
AUN-POL-0026-XX
Pole array for 4 projector




Ordering Code:
AUN-POL-0027-XX
Pole array for 6 projector




Ordering Code:
AUN-CAB-0005-00
Cable H05RN-F 2x1sqmm,
L= 500, with UniBlock
anti-humidity kit,
pre-assembly from factory



Ordering Code:
AUN-SOF-0004-00
Flat beam lens,
HIT-TC-CE, pre-assembly
from factory



Ordering Code:
AUN-SOF-0011-00
Softening lens, HIT-CE,
pre-assembly from factory




Ordering Code:
AUN-GHS-0007-XX
Glare shield cap

KUBIK

KUBIK – GROUND MOUNT PROJECTOR



LAST UPDATE: 15-05-2024



Ordering Code:
AUN-GSH-0036-01
Barn door shield



Ordering Code:
AUN-GHS-0005-11
Glare shield ring, HIT-CE



Ordering Code:
ALUMINUM-POLE-FOR-KUBIK-POLE
Please contact Sales
Representative



Ordering Code:
STEEL-POLE-FOR-KUBIK-POLE
Please contact Sales
Representative