# POLKA

Polka – Cv

SPOTLIGHT

## 

LAST UPDATE: 19-03-2025




The POLKA family of projectors and ground-recessed luminaires is characterized by a small size. The forged aluminum housing exhibits exceptional strength against mechanical impact and corrosion resistance. Several light distributions and color temperatures are available as a standard option. POLKA is equipped with the UniBlock anti-humidity kit for improved reliability and resilience against ingress of moisture. POLKA is also available in stainless steel, refer to the ATOM family for details.


## Technical Data



Ordering Code : 5983-B-2-525-13 Lamp : LED 28° Beam : CCT : 2700 K CRI : CRI >80 SDCM : SDCM = 3 Lamp Lumen : 260 lm Luminaire Lumen : 120 lm Lamp Wattage : 2.1 W[12Vdc/24Vdc] Luminaire Wattage : 2.1 W 57 lm/W Efficacy : Ambient Temperature : 50°C L80B10 >108,000 h Lumen Maintenance Controller : Remote Input Voltage : 24Vdc Net Weight : – kg.



Ordering code guide



### 

Icon definition

Unilamp Co., Ltd. 461 Ramintra Road, Kannayao, Bangkok 10230 Thailand Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1 Fax : +66[0]2 943 2419 online@unilamp.co.th www.unilamp.co.th

# POLKA

Polka – CV Spotlight

## **Unilamp**

LAST UPDATE: 19-03-2025


### Specification


## IEC Standard

	IEC 60598-2-1 Fixed Luminaires
Protection	IP67 Class III
Luminaires Body Housing	Extruded Aluminium S6063 alloy body with low copper content.
Diffuser	Tempered safety glass cover
Gasket	Durable silicone gasket
External Screws	External screws made of stainless steel
Led	High efficiency LED module
Driver	Driver is not included and has to be ordered separately.
Pre-Wire Cable	Pre-wired with 2x0.5mm. cable
Caution	Installation work has to be carried on according to the enclosed installation manual.

IEC 60598-1 General Requirement

## Light Distribution






# POLKA

Polka – CV Spotlight

#### LAST UPDATE: 19-03-2025

## 


### Accessories




Ordering Code: AUN-SOF-0055-00 Softening filter, LED, pre-assembly from factory



Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W




Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 150W




Ordering Code: AUN-DRG-0118-00 LED constant voltage driver, 24VDC, 30W



Ordering Code: AUN-CON-0024-00 IP68 Connector, cable diameter 4.8-6mm, qel-filled



Ordering Code: AUN-DRG-0100-00 LED constant voltage driver, 24VDC, 60W, DALI



Ordering Code: AUN-DRG-0024-00 LED constant voltage driver, 24VDC, 200W



Ordering Code: AUN-DRG-0101-00 LED constant voltage driver, 24VDC, 120W, DALI