DARIUS

DARIUS


WALL SURFACE LIGHT



LAST UPDATE: 24-06-2025



DARIUS is a circular-shaped surface-mount light featuring a robust aluminum housing and impact-resistant polycarbonate lens cover. Its diffused light distribution provides general illumination in private, public, and commercial areas. DARIUS is available with AC COB LED or E27 lamp holder for compact fluorescent, or retrofit LED lamps. The lens cover is designed with a twist-lock mechanism, which allows for simple and secure installation and re-lamping procedures. The high protection rating of IP65 and IK09 allows DARIUS to be installed in the majority of outdoor environments.



Technical Data



Ordering Code: 7071-0-2-493-XX Lamp: Led Retrofit A60

Socket E27

CCT: 2700-6500 K

Lamp Wattage: 5-9 W Ambient Temperature: 25°C Controller: On-Off

Input Voltage: 220-240Vac 50/60Hz

Net Weight: kg.

Ordering code guide

XXXX-X-X-XXX-XX

Product Code

Reflector C D E Electrical Component

Lamp Color

Icon definition

online@unilamp.co.th www.unilamp.co.th

DARIUS

DARIUS

WALL SURFACE LIGHT



LAST UPDATE: 24-06-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP65 Class I

Luminaires Body Housing High-pressure Die Cast Aluminium alloy body and components.

Coating Process UV stablized polyester powder coat.

Diffuser Vandal proof PC diffuser
Gasket Durable silicone gasket

External Screws made of stainless steel

Lamp Holder E27 lampholder

Caution Installation work has to be carried on according to the enclosed installation manual.

Color



Light Distribution

