

# CORE

## MAXI CORE – POLE LIGHT / DOUBLE SIDED


### POLE LIGHTS & POLE TOP LIGHTS



LAST UPDATE: 19-02-2024



Characterized by clean and clear-cut lines CORE is a family of square wall light, ceiling light, bollard and pole lights. CORE is available in two sizes and equipped with COB LED/ High Power LED in three color temperatures with exceptional color consistency. It is also available in HID version as well as with E27 holder for Led Retrofit lamps. The computer-aided-design of the parabolic reflector provides a quality light distribution. The housing is dust and water protected through the extensive engineering design and testing. CORE is recommended to illuminate columns, facades, walkways, parks and various architectural design works. The pole lights give a great level of downward light with symmetric wide beam, asymmetric forward throw or side throw light distributions.



### Technical Data



|                       |                    |
|-----------------------|--------------------|
| Ordering Code :       | 7227-5-3-892-XX    |
| Lamp :                | LED                |
| Beam :                | 17°                |
| CCT :                 | 4000 K             |
| CRI :                 | CRI >80            |
| SDCM :                | SDCM = 3           |
| Lamp Lumen :          | 2x8980 lm          |
| Luminaire Lumen :     | 13720 lm           |
| Lamp Wattage :        | 2x52 W             |
| Luminaire Wattage :   | 112 W              |
| Efficacy :            | 122 lm/W           |
| Ambient Temperature : | 40°C               |
| Lumen Maintenance     | L70B10 >60,000 h   |
| Controller :          | On-Off             |
| Input Voltage :       | 220-240Vac 50/60Hz |
| Net Weight :          | 25.30 kg.          |

### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

A Product Code  
B Reflector  
C Electrical Component  
D Lamp  
E Color



Icon definition

\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# CORE

## MAXI CORE – POLE LIGHT / DOUBLE SIDED

### POLE LIGHTS & POLE TOP LIGHTS





LAST UPDATE: 19-02-2024

#### Specification

|                         |  |  |          |  |             |  |              |  |                     |  |          |  |                 |
|-------------------------|--|--|----------|--|-------------|--|--------------|--|---------------------|--|----------|--|-----------------|
| IEC Standard            | IEC 60598-1 General Requirement<br>IEC 60598-2-1 Fixed Luminaires  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Protection              | IP65 Class I   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| IK Rating               | Protection against mechanical impact IK08 on body and IK07 optical part.   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Luminaires Body Housing | High-pressure Die Cast Aluminium alloy body and components.<br>Extruded Aluminium S6063 alloy body with low copper content.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Coating Process         | Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.                          |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Diffuser                | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Reflector               | High performance anodized spun aluminium reflector.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Gasket                  | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| External Screws         | External screws are in stainless steel with protection grease.   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Cable Entry             | Cable entry protected by weather proof grommet. To be used with HO5RN-F/ HO7RN-F cable with 7-10mm. diameter.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Led                     | High efficiency LED module in COB technology. Assembled on MCPCB and mounted on to heat conductive material.   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Driver                  | High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard.   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Enhanced Protection     | The luminaire is equipped with a 10kV surge protection device, the function of the protector is indicated by a LED, performance in compliance with IEC61643-11.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Internal Wire           | Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Terminal Block          | Terminal block in GFR PA6.6 for cable with cross section up to 4 sqmm. VDE approved.<br>Class1 luminaire provided with the earth connection.   |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Caution                 | Installation work has to be carried on according to the enclosed installation manual.  |  |          |  |             |  |              |  |                     |  |          |  |                 |
| Color                   | <table><tr><td></td><td>Black 01</td></tr><tr><td></td><td>Graphite 02</td></tr><tr><td></td><td>Dark Grey 03</td></tr><tr><td></td><td>Aluminium Silver 04</td></tr><tr><td></td><td>White 06</td></tr><tr><td></td><td>Wooden Brown 07</td></tr></table> |  | Black 01 |  | Graphite 02 |  | Dark Grey 03 |  | Aluminium Silver 04 |  | White 06 |  | Wooden Brown 07 |
|                         | Black 01   |  |          |  |             |  |              |  |                     |  |          |  |                 |
|                         | Graphite 02  |  |          |  |             |  |              |  |                     |  |          |  |                 |
|                         | Dark Grey 03   |  |          |  |             |  |              |  |                     |  |          |  |                 |
|                         | Aluminium Silver 04  |  |          |  |             |  |              |  |                     |  |          |  |                 |
|                         | White 06   |  |          |  |             |  |              |  |                     |  |          |  |                 |
|                         | Wooden Brown 07  |  |          |  |             |  |              |  |                     |  |          |  |                 |

#### Light Distribution



\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# CORE

MAXI CORE – POLE LIGHT / DOUBLE  
SIDED


POLE LIGHTS & POLE TOP LIGHTS



Unilamp

LAST UPDATE: 19-02-2024

## Bug Report



| Lum. Classification System [LCS] |           |          |       |       |
|----------------------------------|-----------|----------|-------|-------|
| LCS                              | Zone      | %Lumens  | %Lamp | %Lum  |
| FL                               | [0-30]    | 3174.0   | 35.3  | 46.3  |
| FM                               | [30-60]   | 152.6    | 1.7   | 2.2   |
| FH                               | [60-80]   | 3.7      | 0.0   | 0.1   |
| FVH                              | [80-90]   | 0.5      | 0.0   | 0.0   |
| BL                               | [0-30]    | 3365.3   | 37.5  | 49.1  |
| BM                               | [30-60]   | 155.8    | 1.7   | 2.3   |
| BH                               | [60-80]   | 3.6      | 0.0   | 0.1   |
| BVH                              | [80-90]   | 0.5      | 0.0   | 0.0   |
| UL                               | [90-100]  | 0.0      | 0.0   | 0.0   |
| UH                               | [100-180] | 3.8      | 0.0   | 0.1   |
| Total                            |           | 6859.8   | 76.2  | 100.0 |
| BUG Rating                       |           | B4-U1-G0 |       |       |

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

# CORE


## MAXI CORE – POLE LIGHT / DOUBLE SIDED

### POLE LIGHTS & POLE TOP LIGHTS



LAST UPDATE: 19-02-2024

#### Accessories



Ordering Code:  
AUN-GHS-0022-00  
Glare Shield Ring for COB



Ordering Code:  
AUN-ACB-0006-00  
Anchor Bolt Kit