# **NEOS**

### **NEOS**


POLE MOUNTED LIGHT



LAST UPDATE: 25-09-2025



NEOS is a small sized high performing area light. Outstanding optical efficacy, high ambient temperature rating and a wide range of mounting accessory makes NEOS a highly competitive product. The smooth curved design eliminates accumulation of water and dust. The unobtrusive slim design is a great match for commercial and residential lighting tasks. The area light can be either equipped with a photocell, DALI-2 control or basic on-off control gear. NEOS can be equipped with mounting accessories for pole integrated mounting, pole bracket, wall and wall corner. The pole bracket is suitable for Pole diameters up to 105mm.



## **Technical Data**

5NI Ordering Code: 7246-U-3-668-XX LED Lamp: Beam: T1 CCT: 3000 K CRI >80 CRI: SDCM: SDCM = 3Lamp Lumen: 4220 lm Luminaire Lumen : 3300 lm Lamp Wattage: 23 W Luminaire Wattage: 25 W Efficacy: 132 lm/W Ambient Temperature : 50°C Lumen Maintenance L70B10 >72,000 h

Controller : On-Off

Input Voltage: 220–240Vac 50/60Hz

Net Weight: 4.00 kg.



Icon definition

# **NEOS**

#### **NEOS**

## POLE MOUNTED LIGHT



LAST UPDATE: 25-09-2025

#### Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP66 Class I

IK Rating Protection against mechanical impact IKO8 on body and optical part.

Luminaires Body Housing High-pressure die cast aluminum alloy body and components.

Extruded aluminum S6063 alloy body with low copper content.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Adjustable Optic Adjustable aiming unit through graduated scale.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by weather proof grommet. To be used with HO5RN-F/ HO7RN-F cable with 6-13mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver High quality constant current LED driver. Conform to safety standard and electromagnetic compatibility standard.

Enhanced Protection The luminaire is equipped with a 10kV surge protection device, the function of the protector is indicated by a LED, performance in

compliance with IEC61643-11.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Terminal Block Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.

Class1 luminaire provided with the earth connection.


Pre-Wire Cable Pre-wired with 3x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.


Caution Installation work has to be carried on according to the enclosed installation manual.

Color



### Light Distribution





# **NEOS**

### **NEOS**

POLE MOUNTED LIGHT



LAST UPDATE: 25-09-2025

#### Accessories



Ordering Code: AUN-SEN-0001-00 Photocell, On-Off, pre-assembly from factory



Ordering Code: AUN-GHS-0032-XX Glare shield cap, pre-assembly from factory



Ordering Code: AUN-ACB-0009-00 Anchor bolt kit, pole diameter 114 and 114/140, galvanized steel pole



Ordering Code: AUN-ACB-0008-00 Anchor bolt kit, pole diameter 102mm and 151x102mm, galvanized steel pole



Ordering Code: AUN-ACB-0005-00 Anchor bolt kit, aluminum pole



Ordering Code: ALUMINUM-POLE-FOR-NEOS Please contact Sales Representative



Ordering Code: STEEL-POLE-FOR-NEOS Please contact Sales Representative