

VAREE

VAREE – CC


UNDERWATER



LAST UPDATE: 17-06-2024



VAREE A family of LED underwater luminaires that is suitable to be installed on the ground, recess in a concrete wall or surface mounted. Operating with high lumen output LED from 2700K, 3000K, 4000K and RGBW with high CRI in 3 steps SDCM. VAREE is designed to illuminate swimming pools, decorative pools, fountains and any submersible application. A wide range of beam angles including Narrow, Medium, Wide and Elliptical beams as well as Asymmetric floor washer. VAREE is pre-wired with underwater cable and internally potted to prevent humidity and condensation. To avoid over-heating, VAREE is equipped with a thermal cut-off device thus the luminaire has to be submerged at all time. The marine grade 316 stainless steel material and advance polymer guarantees corrosion free appearance through out the life time. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.



Technical Data



| | |
|-----------------------|---------------------------------------|
| Ordering Code : | 7413-K-2-686-92 |
| Lamp : | LED |
| Beam : | Asymmetric |
| CCT : | RGBW |
| CRI : | CRI >40 |
| SDCM : | SDCM = 5 |
| Lamp Lumen : | 2370lm |
| Luminaire Lumen : | 1560 lm |
| Lamp Wattage : | 24 W[700mA] |
| Luminaire Wattage : | 24 W |
| Efficacy : | 65 lm/W |
| Ambient Temperature : | 50°C |
| Lumen Maintenance | L70B10 >66,000 h |
| Controller : | Remote |
| Input Voltage : | 700mA, 4CHx5Vdc-6.5Vdc, Uin max 30Vdc |
| Net Weight : | 1.80 kg. |

Ordering code guide

XXXX-X-X-XXX-XX

B
D

A
C
E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition



*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
 461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
 Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1
 Fax : +66[0]2 943 2419
 online@unilamp.co.th
 www.unilamp.co.th


Specification

| | |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IEC Standard | IEC 60598-1 General Requirement IEC 60598-2-18 Luminaires for Swimming Pools |
| Protection | IP68 Class III |
| IK Rating | Protection against mechanical impact IK05 on body and IK07 optical part. |
| Luminaires Body Housing | Supreme corrosion proof Under Water grade Stainless Steel. Injected GFR Engineering Polymer body component. Wall recessed housing made of GFR polymer. |
| Diffuser | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. |
| Lens | Molded PC lens from renowned manufacturers in various light distribution patterns. |
| Gasket | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C. |
| External Screws | Marine grade 316 stainless steel screw. |
| Cable Entry | Cable entry protected by M16 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 5-10mm. diameter. |
| Led | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material. |
| Driver | Driver is not included and has to be ordered separately. |
| Internal Wire | Tinned copper conductor with PTFE insulated internal wire. IMQ approved. Working temperature -40°C to +250°C. |
| Pre-Wire Cable | Pre-wired with 5x1.0 sqmm. PP + TPE cable. VDE approved. |
| Caution | Installation work has to be carried on according to the enclosed installation manual. To avoid over-heating, this luminaire has to use under water only. |

Light Distribution



Accessories




Ordering Code:
AUN-CON-0008-00
IP68 Connector, cable diameter 8-10mm, gel-filled for through wiring, 1-10V or DALI



Ordering Code:
AUN-CON-0009-00
IP68 connection device, cable diameter 5-9.5mm, On-Off




Ordering Code:
AUN-CON-0010-00
IP68 connection device 3 pole, cable diameter 5-9.5mm, with distribution block




Ordering Code:
AUN-DRG-0011-00
LED constant voltage driver, 24VDC, 150W



Ordering Code:
AUN-DRG-0019-01
RGBW LED constant current driver (SELV output), 4x700mA, 4x25W, with IP66 aluminum enclosure, DALI, with 10kV Surge protection



Ordering Code:
AUN-DRG-0024-00
LED constant voltage driver, 24VDC, 200W



Ordering Code:
AUN-DRG-0027-00
LED constant voltage driver, 24VDC, 72W



Ordering Code:
AUN-DRG-0112-01
LED constant current decoder, 4x700mA, 4x23W, with IP67 GFR polymer enclosure, DMX512/RDM



Ordering Code:
AUN-DMX-0023-00
DMX controller, Nicolaudie STICK-KE2



Ordering Code:
AUN-DMX-0024-00
DMX controller, Nicolaudie SLESA-U9



Ordering Code:
AUN-DMX-0025-00
DMX controller, Nicolaudie SLESA-U10



Ordering Code:
AUN-DMX-0026-00
XLR 3 pin male connector, cable UNITRONIC Li2YCYv, L= 1000, DMX

VAREE

VAREE – CC

UNDERWATER

 **Unilamp**

LAST UPDATE: 17-06-2024




Ordering Code:
AUN-DMX-0027-01
Splitter, IP67 aluminum enclosure, DMX




Ordering Code:
AUN-CON-0022-00
IP67 connection device, cable diameter 4.5-11mm, DMX




Ordering Code:
AUN-CON-0023-00
IP67 connection device, cable diameter 4.5-11mm, distribution block, DMX



Ordering Code:
ATR-CAB-0006-00
Cable UNITRONIC Li2YCYv, L= 2000mm, DMX




Ordering Code:
AUN-CAB-0040-00
Cable H07RN-F 2x1sqmm, L= 2000mm



Ordering Code:
AUN-CAB-0039-00
Cable H07RN-F 3x1sqmm, L= 2000mm



Ordering Code:
AUN-CTR-0001-00
Touch panel, EDT4, RGBW, DALI



Ordering Code:
AUN-CTR-0002-00
Bus power supply, 15VDC 220mA, 3.3W, DALI

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1
Fax : +66[0]2 943 2419
online@unilamp.co.th
www.unilamp.co.th