VAREE


VAREE SPOT LIGHT


UNDERWATER LIGHT

LAST UPDATE: 19-03-2025



VAREE A family of LED underwater luminaires that is suitable to be installed on the ground, recess in a concrete wall or surface mounted. Operating with high lumen output LED from 2700K, 3000K, 4000K and RGBW with high CRI in 3 steps SDCM. VAREE is designed to illuminate swimming pools, decorative pools, fountains and any submersible application. A wide range of beam angles including Narrow, Medium, Wide and Elliptical beams as well as Asymmetric floor washer. VAREE is pre-wired with underwater cable and internally potted to prevent humidity and condensation. To avoid over-heating, VAREE is equipped with a thermal cut-off device thus the luminaire has to be submerged at all time. The marine grade 316 stainless steel material and advance polymer guarantees corrosion free appearance through out the life time. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.





Icon definition

Technical Data



Ordering Code : 7415-B-2-524-92 Lamp : LED 25° Beam : CCT : 2700 K CRI : CRI >80 SDCM : SDCM = 3 Lamp Lumen : 2160 lm Luminaire Lumen : 1260 lm Lamp Wattage : 18 W(24Vdc) Luminaire Wattage : 18 W 70 lm/W Efficacy : Ambient Temperature : 50°C Lumen Maintenance L70B10 >66,000 h Controller : Remote Input Voltage : 24Vdc Net Weight : 1.30 kg.

Unilamp Co., Ltd. 461 Ramintra Road, Kannayao, Bangkok 10230 Thailand Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1 Fax : +66[0]2 943 2419 online@unilamp.co.th www.unilamp.co.th

VAREE

VAREE SPOT LIGHT

UNDERWATER LIGHT


Unilamp


LAST UPDATE: 19-03-2025

Specification

IEC Standard	IEC 60598-1 General Requirement
	IEC 60598-2-18 Luminaires for Swimming Pools
Protection	IP68 Class III
Luminaires Body Housing	Corrosion resistant stamped 316 stainless steel body.
	Full body polish finished.
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
Lens	Molded PC lens from renowned manufacturers in various light distribution patterns.
Adjustable Optic	Adjustable aiming unit through graduated scale.
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.
External Screws	Marine grade 316 stainless steel screw.
Cable Entry	Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.
Driver	Driver is not included and has to be ordered separately.
Internal Wire	Tinned copper conductor with PTFE insulated internal wire. IMQ approved. Working temperature -40°C to +250°C.
Pre-Wire Cable	Pre-wired with 2x1.0 sqmm. H05RN-F neoprene cable. IMQ approved.
Caution	Installation work has to be carried on according to the enclosed installation manual.
	To avoid over-heating, this luminaire has to use under water only.

Light Distribution








VAREE SPOT LIGHT

UNDERWATER LIGHT


LAST UPDATE: 19-03-2025

Unilamp

Accessories



Ordering Code: AUN-SOF-0017-00 Softening filter, LED, pre-assembly from factory



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 150W



Ordering Code: AUN-CON-0024-00 IP68 Connector, cable diameter 4.8-6mm, qel-filled



Ordering Code: AUN-CON-0003-00 IP68 Connector, cable diameter 8-10mm, gel-filled for through wiring



Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W