

# VAREE

## VAREE SPOT LIGHT


### UNDERWATER



LAST UPDATE: 14-05-2024



VAREE A family of LED underwater luminaires that is suitable to be installed on the ground, recess in a concrete wall or surface mounted. Operating with high lumen output LED from 2700K, 3000K, 4000K and RGBW with high CRI in 3 steps SDCM. VAREE is designed to illuminate swimming pools, decorative pools, fountains and any submersible application. A wide range of beam angles including Narrow, Medium, Wide and Elliptical beams as well as Asymmetric floor washer. VAREE is pre-wired with underwater cable and internally potted to prevent humidity and condensation. To avoid over-heating, VAREE is equipped with a thermal cut-off device thus the luminaire has to be submerged at all time. The marine grade 316 stainless steel material and advance polymer guarantees corrosion free appearance through out the life time. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.



### Technical Data



|                       |                  |
|-----------------------|------------------|
| Ordering Code :       | 7415-C-2-898-92  |
| Lamp :                | LED              |
| Beam :                | 46°              |
| CCT :                 | 4000 K           |
| CRI :                 | CRI >80          |
| SDCM :                | SDCM = 3         |
| Lamp Lumen :          | 3090 lm          |
| Luminaire Lumen :     | 1650 lm          |
| Lamp Wattage :        | 25 W[24Vdc]      |
| Luminaire Wattage :   | 25 W             |
| Efficacy :            | 66 lm/W          |
| Ambient Temperature : | 50°C             |
| Lumen Maintenance     | L70B10 >66,000 h |
| Controller :          | Remote           |
| Input Voltage :       | 24Vdc            |
| Net Weight :          | 1.30 kg.         |

#### Ordering code guide

XXXX-X-X-XXX-XX

A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition



\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

### Specification

|                         |   |
|-------------------------|---|
| IEC Standard            | IEC 60598-1 General Requirement<br>IEC 60598-2-18 Luminaires for Swimming Pools   |
| Protection              | IP68 Class III  |
| Luminaires Body Housing | Corrosion resistant stamped 316 stainless steel body.<br>Full body polish finished.   |
| Diffuser                | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.  |
| Lens                    | Molded PC lens from renowned manufacturers in various light distribution patterns.  |
| Adjustable Optic        | Adjustable aiming unit through graduated scale.   |
| Gasket                  | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.   |
| External Screws         | Marine grade 316 stainless steel screw.   |
| Cable Entry             | Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.  |
| Led                     | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.                  |
| Driver                  | Driver is not included and has to be ordered separately.  |
| Internal Wire           | Tinned copper conductor with PTFE insulated internal wire. IMQ approved. Working temperature -40°C to +250°C.   |
| Pre-Wire Cable          | Pre-wired with 2x1.0 sqmm. HO5RN-F neoprene cable. IMQ approved.  |
| Caution                 | Installation work has to be carried on according to the enclosed installation manual.<br>To avoid over-heating, this luminaire has to use under water only. |

### Light Distribution



# VAREE

## VAREE SPOT LIGHT UNDERWATER



LAST UPDATE: 14-05-2024

### Accessories




Ordering Code:  
AUN-SOF-0017-00  
Softening Filter  
[pre-assembled from  
factory]



Ordering Code:  
AUN-DRG-0011-00  
LED Constant Voltage  
Driver 24Vdc 150W.



Ordering Code:  
AUN-CON-0024-00  
Gel-Filled IP68 Connector  
Cable Diameter 4.8 – 6mm.



Ordering Code:  
AUN-CON-0003-00  
Gel-Filled IP68 Connector  
for Through Wiring Cable  
Diameter 6.5 – 12mm.



Ordering Code:  
AUN-DRG-0027-00  
LED Constant Voltage  
Driver 24Vdc 72W.

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th