

# VAREE

VAREE – CC


UNDERWATER

 **Unilamp**

LAST UPDATE: 19-03-2025



VAREE A family of LED underwater luminaires that is suitable to be installed on the ground, recess in a concrete wall or surface mounted. Operating with high lumen output LED from 2700K, 3000K, 4000K and RGBW with high CRI in 3 steps SDCM. VAREE is designed to illuminate swimming pools, decorative pools, fountains and any submersible application. A wide range of beam angles including Narrow, Medium, Wide and Elliptical beams as well as Asymmetric floor washer. VAREE is pre-wired with underwater cable and internally potted to prevent humidity and condensation. To avoid over-heating, VAREE is equipped with a thermal cut-off device thus the luminaire has to be submerged at all time. The marine grade 316 stainless steel material and advance polymer guarantees corrosion free appearance through out the life time. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.



## Technical Data



Ordering Code :	7415-H-2-686-92
Lamp :	LED
Beam :	44°/10°
CCT :	RGBW
CRI :	CRI >40
SDCM :	SDCM = 5
Lamp Lumen :	2370lm
Luminaire Lumen :	1330 lm
Lamp Wattage :	24 W[700mA]
Luminaire Wattage :	24 W
Efficacy :	55 lm/W
Ambient Temperature :	50°C
Lumen Maintenance	L70B10 >66,000 h
Controller :	Remote
Input Voltage :	700mA, 4CHx5Vdc-6.5Vdc, Uin max 30Vdc
Net Weight :	1.40 kg.

### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition



\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

### Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-18 Luminaires for Swimming Pools
Protection	IP68 Class III
Luminaires Body Housing	Corrosion resistant stamped 316 stainless steel body. Full body polish finished.
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
Lens	Molded PC lens from renowned manufacturers in various light distribution patterns.
Adjustable Optic	Adjustable aiming unit through graduated scale.
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.
External Screws	Marine grade 316 stainless steel screw.
Cable Entry	Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.
Driver	Driver is not included and has to be ordered separately.
Internal Wire	Tinned copper conductor with PTFE insulated internal wire. IMQ approved. Working temperature -40°C to +250°C.
Pre-Wire Cable	Pre-wired with 5x1.0 sqmm. PP + TPE cable. VDE approved.
Caution	Installation work has to be carried on according to the enclosed installation manual. To avoid over-heating, this luminaire has to use under water only.

### Light Distribution



#### Accessories




Ordering Code:  
AUN-CON-0008-00  
IP68 Connector, cable diameter 8-10mm, gel-filled for through wiring, 1-10V or DALI




Ordering Code:  
AUN-CON-0009-00  
IP68 connection device, cable diameter 5-9.5mm, On-Off



Ordering Code:  
AUN-CON-0010-00  
IP68 connection device 3 pole, cable diameter 5-9.5mm, with distribution block



Ordering Code:  
AUN-GSH-0012-00  
Honeycomb louver, LED, pre-assembly from factory




Ordering Code:  
AUN-SOF-0026-00  
Softening filter, LED, pre-assembly from factory




Ordering Code:  
AUN-DRG-0011-00  
LED constant voltage driver, 24VDC, 150W



Ordering Code:  
AUN-DRG-0019-01  
RGBW LED constant current driver [SELV output], 4x700mA, 4x25W, with IP66 aluminum enclosure, DALI, with 10kV Surge protection




Ordering Code:  
AUN-DRG-0024-00  
LED constant voltage driver, 24VDC, 200W



Ordering Code:  
AUN-DRG-0027-00  
LED constant voltage driver, 24VDC, 72W



Ordering Code:  
AUN-DRG-0112-01  
LED constant current decoder, 4x700mA, 4x23W, with IP67 GFR polymer enclosure, DMX512/RDM



Ordering Code:  
AUN-DMX-0023-00  
DMX controller, Touchscreen



Ordering Code:  
AUN-DMX-0024-00  
DMX controller, 1-Channel

# VAREE

## VAREE – CC

### UNDERWATER



LAST UPDATE: 19-03-2025



Ordering Code:  
AUN-DMX-0025-00  
DMX controller, 2-Channel



Ordering Code:  
AUN-DMX-0026-00  
DMX Connector, 3 pin  
male, L= 1000mm




Ordering Code:  
AUN-DMX-0027-01  
Splitter, IP67 aluminum  
enclosure, DMX




Ordering Code:  
AUN-CON-0022-00  
IP67 connection device,  
cable diameter 4.5-11mm,  
DMX




Ordering Code:  
AUN-CON-0023-00  
IP67 connection device,  
cable diameter 4.5-11mm,  
distribution block, DMX



Ordering Code:  
ATR-CAB-0006-00  
Cable signal, L= 2000mm,  
DMX



Ordering Code:  
AUN-CAB-0040-00  
Cable H07RN-F 2x1sqmm,  
L= 2000mm



Ordering Code:  
AUN-CAB-0039-00  
Cable H07RN-F 3x1sqmm,  
L= 2000mm



Ordering Code:  
AUN-CTR-0001-00  
Touch panel, EDT4, RGBW,  
DALI



Ordering Code:  
AUN-CTR-0002-00  
Bus power supply, 15VDC  
220mA, 3.3W, DALI

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th