ACQUA

ACQUA


UNDERWATER LIGHT




LAST UPDATE: 11-11-2025



A family of recessed and surface mounted under water luminaires which are commonly used to illuminate swimming pools, decorative pools and fountains. Accessories include several watertight connecting devices. ACQUA1 utilizes high power LED in 2700K, 3000K or 4000K and high quality optical lenses offering narrow, medium, wide and elliptical beam. Version with GU5.3 lamp holder for MR16 Led retrofit lamps is also available. To avoid installation issues and add another level of safety, ACQUA1 is pre-wired and is fitted with an anti-condensation device. To avoid over-heating of the luminaire body, ACQUA1 must be operated in a submersible state at all time. The marine grade 316 stainless steel body guarantees corrosion free appearance throughout the life time. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.







Color

Icon definition

Technical Data



Ordering Code : 7416-H-2-585-92

Lamp: LED Beam: 43°/24° CCT: 4000 K CRI: CRI >80 SDCM: SDCM = 3Lamp Lumen: 1390 lm Luminaire Lumen : 910 lm 12 W(24Vdc) Lamp Wattage: Luminaire Wattage: 12 W

Efficacy : 60 lm/W Ambient Temperature : 50°C

Lumen Maintenance L70B10 >66,000 h

Controller: Remote
Input Voltage: 24Vdc
Net Weight: 1.80 kg.



ACQUA

UNDERWATER LIGHT



LAST UPDATE: 11-11-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-18 Luminaires for Swimming Pools

Protection IP68 Class III

IK Rating Protection against mechanical impact IK10 on body and IK09 on optical part.

Luminaires Body Housing Supreme corrosion proof Under Water grade Stainless Steel.

Full body polish finished.

Wall recessed housing made of GFR polymer.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws Marine grade 316 stainless steel screw.

Cable Entry Cable entry protected by M16 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 5-10mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.


Driver Driver is not included and has to be ordered separately.


Pre-Wire Cable Pre-wired with 2x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.

Caution Installation work has to be carried on according to the enclosed installation manual.

The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light Distribution





ACQUA

ACQUA

UNDERWATER LIGHT




LAST UPDATE: 11-11-2025


Accessories



Ordering Code:
AUN-GSH-0008-00
Honeycomb louver, LED,
pre-assembly from factory



Ordering Code: AUN-SOF-0022-00 Softening filter, LED, pre-assembly from factory



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 150W




Ordering Code: AUN-CON-0004-00 IP68 Connector, cable diameter 8-10mm, qel-filled




Ordering Code:
AUN-CON-0003-00
IP68 Connector, cable
diameter 8-10mm,
qel-filled for through wiring




Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W



Ordering Code: AUN-DRG-0118-00 LED constant voltage driver, 24VDC, 30W



Ordering Code: AUN-DRG-0100-00 LED constant voltage driver, 24VDC, 60W, DALI



Ordering Code: AUN-DRG-0101-00 LED constant voltage driver, 24VDC, 120W, DALI



Ordering Code: AUN-DRG-0126-00 LED constant current driver, 250mA, 12W, with IP67 GFR polymer enclosure, On-Off, BLACK