VOLGA

VOLGA/1 – CV WALL RECESS UNDER WATER

UNDERWATER LIGHT



LAST UPDATE: 19-03-2025


VOLGA is a family of robust marine grade stainless steel luminaires suitable for underwater and ground and well recessed mounting. It utilizes high power LED in available with different color temperatures. The high quality optical lenses offering beams from ultra-narrow to wide and asymmetric light distributions. VOLGA is a perfect choice to illuminate swimming pools, decorative pools and fountains and narrow columns. The luminaire is supplied with pre-wired cable, anti-humidity kit and is fully sealed from the factory. The underwater version must be operated submersed in water at all time in order to prevent over-heating of the luminaire. VOLGA inground and wall recessed is suitable for in air operation. The marine grade 316 stainless steel body guarantees corrosion free appearance throughout the lifetime. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.

Technical Data



7418-0-2-431-91
LED
4000 K
CRI >80
SDCM = 3
390 lm
40 lm
3.3 W(24Vdc)
3.3 W
12 lm/W
50°C
L80B10 >108,000 h
Remote
24Vdc
– kg.

Ordering code guide



IK BODY OPTIC

Icon definition

Ø1"

Unilamp Co., Ltd. 461 Ramintra Road, Kannayao, Bangkok 10230 Thailand Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1 Fax : +66[0]2 943 2419 online@unilamp.co.th www.unilamp.co.th

VOLGA

VOLGA/1 – CV WALL RECESS UNDER WATER

UNDERWATER LIGHT


Unilamp


LAST UPDATE: 19-03-2025

Specification

IEC 60598-1 General Requirement
IEC 60598-2-18 Luminaires for Swimming Pools
IP68 Class III
Supreme corrosion proof Under Water grade Stainless Steel.
Recessed housing made of GFR polymer.
Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.
External screws are in stainless steel with protection grease.
Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.
High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.
Driver is not included and has to be ordered separately.
Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Pre-wired with 2x1.0 sqmm. H05RN-F neoprene cable. IMQ approved.
Installation work has to be carried on according to the enclosed installation manual.
The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light Distribution





VOLGA

VOLGA/1 - CV WALL RECESS UNDER WATER

UNDERWATER LIGHT

Accessories

Ordering Code:

Ordering Code:

AUN-DRG-0118-00

LED constant voltage

driver, 24VDC, 30W


AUN-DRG-0011-00


LED constant voltage

driver, 24VDC, 150W


b

Ordering Code: AUN-CON-0024-00







Ordering Code: AUN-DRG-0100-00 LED constant voltage driver, 24VDC, 60W, DALI



Ordering Code: AUN-DRG-0024-00 LED constant voltage driver, 24VDC, 200W



Ordering Code: AUN-DRG-0101-00 LED constant voltage driver, 24VDC, 12OW, DALI



Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W

Unilamp Co., Ltd. 461 Ramintra Road, Kannayao, Bangkok 10230 Thailand Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1 Fax : +66[0]2 943 2419 online@unilamp.co.th www.unilamp.co.th

LAST UPDATE: 19-03-2025