VOLGA

VOLGA/1 – CV WALL RECESS UNDER WATER


UNDERWATER LIGHT







VOLGA is a family of robust marine grade stainless steel luminaires suitable for underwater and ground and well recessed mounting. It utilizes high power LED in available with different color temperatures. The high quality optical lenses offering beams from ultra-narrow to wide and asymmetric light distributions. VOLGA is a perfect choice to illuminate swimming pools, decorative pools and fountains and narrow columns. The luminaire is supplied with pre-wired cable, anti-humidity kit and is fully sealed from the factory. The underwater version must be operated submersed in water at all time in order to prevent over-heating of the luminaire. VOLGA inground and wall recessed is suitable for in air operation. The marine grade 316 stainless steel body guarantees corrosion free appearance throughout the lifetime. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.



Technical Data

CE | IP68 (II) [8]

Ordering Code : 7418-U-2-373-91

Lamp : LED

 Beam :
 Asymmetric

 CCT :
 3000 K

 CRI :
 CRI > 80

 SDCM :
 SDCM = 3

 Lamp Lumen :
 660 lm

 Luminaire Lumen :
 210 lm

 Lamp Wattage :
 5.8 W[24Vdc]

Luminaire Wattage : 5.8 W
Efficacy : 36 lm/W
Ambient Temperature : 50°C

Lumen Maintenance L80B10 >145,000 h

Controller : Remote Input Voltage : 24Vdc Net Weight : - kg.



Icon definition

online@unilamp.co.th

www.unilamp.co.th

VOLGA

VOLGA/1 - CV WALL RECESS UNDER WATER

UNDERWATER LIGHT

⊕ Unilamp

LAST UPDATE: 19-03-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-18 Luminaires for Swimming Pools

Protection IP68 Class III

Luminaires Body Housing Supreme corrosion proof Under Water grade Stainless Steel.

Recessed housing made of GFR polymer.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver Driver is not included and has to be ordered separately.


Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.


Pre-Wire Cable Pre-wired with 2x1.0 sqmm. HO5RN-F neoprene cable. IMQ approved.

Caution Installation work has to be carried on according to the enclosed installation manual.

The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light Distribution





VOLGA


VOLGA/1 – CV WALL RECESS UNDER WATER

UNDERWATER LIGHT


LAST UPDATE: 19-03-2025




Accessories



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 150W




Ordering Code: AUN-GSH-0017-00 Honeycomb louver, LED, pre-assembly from factory




Ordering Code: AUN-SOF-0029-00 Softening filter, LED, pre-assembly from factory




Ordering Code: AUN-CON-0024-00 IP68 Connector, cable diameter 4.8-6mm, qel-filled




Ordering Code: AUN-DRG-0024-00 LED constant voltage driver, 24VDC, 200W




Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W



Ordering Code: AUN-DRG-0118-00 LED constant voltage driver, 24VDC, 30W



Ordering Code: AUN-DRG-0100-00 LED constant voltage driver, 24VDC, 60W, DALI



Ordering Code: AUN-DRG-0101-00 LED constant voltage driver, 24VDC, 120W, DALI