

# SIRIUS

SIRIUS 1200


LINEAR LIGHT

 **Unilamp**

LAST UPDATE: 17-06-2024



SIRIUS a brand new linear light family features various mounting application types including in-ground walk over, wall mounted, ceiling mounted, suspension and even permanently submersion stage. SIRIUS utilized the latest LED technology from world renowned manufactures with the choices of multiple light distributions. It offered narrow beam, medium beam, wide beam, asymmetric wall washer, wash glazing, bi-symmetric and much more. Thanks to a screw-less, clear and clean-cut design SIRIUS can be installed in most application where a decent architectural expression is required. Diversity types of connecting accessory is available for this linear light family.



## Technical Data



|                       |                   |
|-----------------------|-------------------|
| Ordering Code :       | 7421-H-2-559-91   |
| Lamp :                | LED               |
| Beam :                | 46°/16°           |
| CCT :                 | 4000 K            |
| CRI :                 | CRI >80           |
| SDCM :                | SDCM = 3          |
| Lamp Lumen :          | 2960 lm           |
| Luminaire Lumen :     | 2060 lm           |
| Lamp Wattage :        | 20 W[24Vdc]       |
| Luminaire Wattage :   | 20 W              |
| Efficacy :            | 103 lm/W          |
| Ambient Temperature : | 50°C              |
| Lumen Maintenance     | L80B10 >108,000 h |
| Controller :          | Remote            |
| Input Voltage :       | 24Vdc             |
| Net Weight :          | 2.80 kg.          |

### Ordering code guide

XXXX-X-X-XXX-XX

A                      B                      C                      D                      E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition

\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(O)2 943 2420-1, +66(O)2 946 4170-1  
Fax : +66(O)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# SIRIUS

## SIRIUS 1200

### LINEAR LIGHT





LAST UPDATE: 17-06-2024

#### Specification

|                         |   |
|-------------------------|---|
| IEC Standard            | IEC 60598-1 General Requirement<br>IEC 60598-2-18 Luminaires for Swimming Pools   |
| Protection              | IP68 Class III  |
| Luminaires Body Housing | Supreme corrosion proof Under Water grade Stainless Steel.<br>Extruded PC body component.   |
| Diffuser                | Self-extinguishing high impact resistant clear polycarbonate diffuser with UV stabilized additive.  |
| Lens                    | Molded PC lens from renowned manufacturers in various light distribution patterns.  |
| Adjustable Optic        | Adjustable aiming unit through graduated scale.   |
| Gasket                  | Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature $-40^{\circ}\text{C}$ to $+200^{\circ}\text{C}$ .                |
| External Screws         | Marine grade 316 stainless steel screw.   |
| Cable Entry             | Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.  |
| Led                     | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.                  |
| Driver                  | Driver is not included and has to be ordered separately.  |
| Internal Wire           | Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature $-40^{\circ}\text{C}$ to $+180^{\circ}\text{C}$ .          |
| Pre-Wire Cable          | Pre-wired with 2x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.<br>Equipped with anti-humidity kit.  |
| Caution                 | Installation work has to be carried on according to the enclosed installation manual.<br>To avoid over-heating, this luminaire has to use under water only. |

#### Light Distribution



\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# SIRIUS


SIRIUS 1200

LINEAR LIGHT

 **Unilamp**

LAST UPDATE: 17-06-2024


## Accessories



Ordering Code:  
AUN-DRG-0011-00  
LED constant voltage  
driver, 24VDC, 150W



Ordering Code:  
AUN-CON-0003-00  
IP68 Connector, cable  
diameter 8-10mm,  
gel-filled for through wiring



Ordering Code:  
AUN-DRG-0027-00  
LED constant voltage  
driver, 24VDC, 72W

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(O)2 943 2420-1, +66(O)2 946 4170-1  
Fax : +66(O)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th