VOLGA

VOLGA/1 - CC GROUND MOUNT


UNDERWATER

LAST UPDATE: 19-03-2025





VOLGA is a family of robust marine grade stainless steel luminaires suitable for underwater and ground and well recessed mounting. It utilizes high power LED in available with different color temperatures. The high quality optical lenses offering beams from ultra-narrow to wide and asymmetric light distributions. VOLGA is a perfect choice to illuminate swimming pools, decorative pools and fountains and narrow columns. The luminaire is supplied with pre-wired cable, anti-humidity kit and is fully sealed from the factory. The underwater version must be operated submersed in water at all time in order to prevent over-heating of the luminaire. VOLGA inground and wall recessed is suitable for in air operation. The marine grade 316 stainless steel body guarantees corrosion free appearance throughout the lifetime. We highly recommend that the luminaire lay out should be considered during specifying and planning processes. Installation work must be carried out under national safety regulations.



Technical Data



Ordering Code : 7431-0-2-367-91

 Lamp:
 LED

 CCT:
 3000 K

 CRI:
 CRI >80

 SDCM:
 SDCM = 3

 Lamp Lumen:
 660 lm

 Luminaire Lumen:
 50 lm

Lamp Wattage : 5.8 W(500mA)


Luminaire Wattage : 5.8 W
Efficacy : 8 lm/W
Ambient Temperature : 50°C

Lumen Maintenance L80B10 >145,000 h

Controller : Remote

Input Voltage: 500mA, 11.55Vdc, Uin max 50Vdc

Net Weight: 0.60 kg.





Icon definition

online@unilamp.co.th

www.unilamp.co.th

VOLGA

VOLGA/1 - CC GROUND MOUNT

UNDERWATER

LAST UPDATE: 19-03-2025



Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP68 Class III

Luminaires Body Housing Supreme corrosion proof Under Water grade Stainless Steel.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by M12 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 4-7mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver Driver is not included and has to be ordered separately.


Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.


Pre-Wire Cable Pre-wired with 2x1.0 sqmm. HO5RN-F neoprene cable. IMQ approved.

Caution Installation work has to be carried on according to the enclosed installation manual.

The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light Distribution





VOLGA

VOLGA/1 - CC GROUND MOUNT

UNDERWATER

LAST UPDATE: 19-03-2025



Accessories



Ordering Code: AUN-CON-0024-00 IP68 Connector, cable diameter 4.8-6mm, gel-filled



Ordering Code: AUN-DRG-0026-00 LED constant current driver, 500mA, 12W, with IP67 GFR polymer enclosure, On-Off