

RADIANT

RADIANT


POLE MOUNTED LIGHT



LAST UPDATE: 01-04-2026



RADIANT is a sleek, cylindrical light column designed to deliver uniform, symmetrical illumination for outdoor environments. With a recommended mounting height of 3–4 meters, it provides effective mid-to-high level lighting suitable for walkways, gardens, parks, open spaces, and commercial landscapes. The luminaire operates with E27 base retrofit LED or compact fluorescent lamps, offering flexibility and efficiency. Equipped with anti-glare suppression louvers, RADIANT ensures comfortable illumination by directing light downward, enhancing visual comfort and reducing light pollution. A clear PMMA cover protects the lamp compartment against dust and water, ensuring durability and long-term performance in outdoor conditions. Designed for reliable installation, RADIANT is compatible with anchor units for concrete foundations, making it a practical and stylish solution for public and residential lighting applications.



Technical Data



Ordering Code :	7702-O-2-407-XX
Lamp :	Led Retrofit E27
Socket :	E27
CCT :	2700-6500 K
Lamp Wattage :	9-12 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	- kg.

Ordering code guide

XXXX-X-X-XXX-XX
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(O)2 943 2420-1, +66(O)2 946 4170-1
Fax : +66(O)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

RADIANT

RADIANT






POLE MOUNTED LIGHT





LAST UPDATE: 01-04-2026

Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP65 Class I
Luminaires Body Housing	Premium high-strength cast aluminum component for durability and performance. Extruded 6063 aluminum body with minimal copper content for corrosion resistance.
Coating Process	Durable UV-resistant polyester powder coat for outdoor applications.
Diffuser	High-performance weather-resistant extruded PMMA with hardened coating.
Reflector	Precision-engineered aluminum louvers reduce glare and enhance control.
Gasket	High-durability silicone gasket for long-lasting sealing performance.
External Screws	Durable stainless steel screws with anti-corrosion grease for extended lifespan.
Lamp Holder	Certified E27 ceramic lampholder designed for high-temperature applications.
Pre-Wire Cable	Certified pre-wired 3x0.75 sqmm cable, featuring HO5RN-F neoprene insulation.
Caution	Installation must be performed as per the provided installation instructions.

Color	 Black O1
	 Graphite O2
	 Dark Grey O3
	 Aluminum Silver O4
	 White O6

Light Distribution



*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1
Fax : +66[0]2 943 2419
online@unilamp.co.th
www.unilamp.co.th

RADIANT

RADIANT

POLE MOUNTED LIGHT

 **Unilamp**

LAST UPDATE: 01-04-2026

Accessories



Ordering Code:

AUN-ACB-0013-00

Anchor bolt kit

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th