NEOPLACE DIRECT


POLE MOUNTED LIGHT



LAST UPDATE: 21-10-2025



NeoPLACE is a family of large wall light and pole—top luminaires with symmetrical low—glare indirect light distribution. The recommended mounting height is between 3 – 5 meters. It is available in LED light sources in 2 different color temperatures 3000K and 4000K with DALI dimming option. NeoPLACE is suitable for the place where glare control is preferred. It is a perfect alternative to replace old—style cone—shaped conventional luminaires. It is suitable to illuminate parking lots, public parks, and pedestrian and open spaces. Available as an option are Aluminium Poles, Galvanized steel poles, and anchorage unit for concrete foundations. NeoPLACE Direct pole top light, the directional illumination option for NeoPLACE. This is an extension of the indirect variant of the modern looking pole—top range. Wider installation spacing, good glare control, increased luminaire efficacy, and minimal amount of uplight are the major improvements. NeoPLACE Direct is available with T2, T3, T4 and T5 light distribution. The ambient temperature rating has been increased to 50°C.



Technical Data



Ordering Code : 7760-L-A-676-XX

Lamp : LED

Beam : T5 - Wide Symmetric

CCT: 2700 K CRI: CRI >80 SDCM: SDCM = 3Lamp Lumen: 4160 lm Luminaire Lumen : 3020 lm Lamp Wattage: 34 W Luminaire Wattage: 36 W Efficacy: 83 lm/W Ambient Temperature : 50°C

Lumen Maintenance L80B10 >108,000 h

Controller: CASAMBI

Input Voltage: 220–240Vac 50/60Hz

Net Weight: 5.00 kg.



Icon definition

online@unilamp.co.th

www.unilamp.co.th

NEOPLACE DIRECT

POLE MOUNTED LIGHT



LAST UPDATE: 21-10-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP66 Class I

IK Rating Protection against mechanical impact IK10 on body and optical part.

Luminaires Body Housing High-pressure die cast aluminum alloy body and components.

Stamped 1100 aluminum.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Self-extinguishing high impact resistant clear polycarbonate diffuser with UV stabilized additive.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Gasket Weather resistant silicone gasket. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver High quality CASAMBI controllable LED driver with constant current output. Conform to applicable safety standards and

electromagnetic compatibility.

Enhanced Protection The luminaire is equipped with a 10kV surge protection device, the function of the protector is indicated by a LED, performance in

compliance with IEC61643-11.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Terminal Block Assembled with quick connector for cable with cross section up to 2.5 sqmm. from ADELS or equivalents. VDE approved.

Class1 luminaire provided with the earth connection.

Pre-Wire Cable Pre-wired with 3x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.


Equipped with anti-humidity kit.


Caution Installation work has to be carried on according to the enclosed installation manual.

Color



Light Distribution






NEOPLACE DIRECT

POLE MOUNTED LIGHT



LAST UPDATE: 21-10-2025

Bug Report



Lum. Classification System (LCS)				
LCS 2	Zone	%Lumens	%Lamp	%Lum
FL [[0-30]	190.9	4.6	6.3
FM ([30-60]	897.1	21.6	29.7
FH [[60-80]	359.6	8.6	11.9
FVH [[80-90]	38.9	0.9	1.3
BL ([0-30]	190.9	4.6	6.3
BM ([30-60]	897.1	21.6	29.7
BH ([60-80]	359.6	8.6	11.9
BVH [[80-90]	38.9	0.9	1.3
UL ([90-100]	25.0	0.6	8.0
UH I	[100-180]	21.6	0.5	0.7
Total		3019.6	72.5	100.0
BUG Rating		B1-U2-G1		

NEOPLACE DIRECT

POLE MOUNTED LIGHT

& Unilamp

LAST UPDATE: 21-10-2025

Accessories



Ordering Code: ALUMINUM-POLE-FOR-NEOPLACE Please contact Sales Representative



Ordering Code: AUN-ACB-0005-00 Anchor bolt kit, aluminum pole