

# ZOID

## ZOID BOLLARD


### BOLLARDS



LAST UPDATE: 22-02-2024



ZOID is a distinctive trapezoid-outlined vertical illuminating low height light column with single sided light emission and perfect glare control. It is a Class 2 luminaire with cutting edge LED technology with absolutely flicker free light emission. LED is available in 3000K and 4000K color temperature with superb color rendering index. T5 version with electronic control gear is also available. The high quality corrosion resistance aluminium housing is filmed with Nano Ceramic and coated with super durable paint. The heat management has been delicately designed and tested under high ambient thermal condition. The height of the bollard can be customized according to specific requirement. An anchorage unit is available as an accessory.



## Technical Data



Ordering Code :	7811-0-3-311-XX
Lamp :	T5
Socket :	G5
CCT :	2700-6500 K
Lamp Lumen :	2x1200 lm
Luminaire Lumen :	2400 lm
Lamp Wattage :	2x14 W
Luminaire Wattage :	28 W
Ambient Temperature :	25°C
Controller :	On-Off
Input Voltage :	220-240Vac 50/60Hz
Net Weight :	5.00 kg.

### Ordering code guide

XXXX-X-X-XXX-XX  
A B C D E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color



Icon definition



\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

## Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP65 Class II
IK Rating	Protection against mechanical impact IK08 on body and IK07 optical part.
Luminaires Body Housing	High-pressure Die Cast Aluminium alloy body and components. Extruded Aluminium S6063 alloy body with low copper content.
Coating Process	Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.
Reflector	High performance CNC forming aluminium reflector sheet.
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.
External Screws	External screws are in stainless steel with protection grease.
Cable Entry	Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.
Lamp Holder	G5 lampholder in PBT body. IMQ/ ENEC approved.
Ballast	Electronic ballast for fluorescent lamp. ENEC approved.
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Terminal Block	Terminal block in GFR PA6.6 for cable with cross section up to 2.5 sqmm. VDE approved.
Caution	Installation work has to be carried on according to the enclosed installation manual.
Color	<div> <div>Black O1</div> <div>Graphite O2</div> <div>Dark Grey O3</div> <div>Aluminium Silver O4</div> <div>White O6</div> <div>Wooden Brown O7</div> </div>

## Light Distribution



# ZOID


## ZOID BOLLARD

### BOLLARDS



LAST UPDATE: 22-02-2024

#### Bug Report



Lum. Classification System (LCS)				
LCS	Zone	%Lumens	%Lamp	%Lum
FL	[0-30]	23.3	1.0	2.8
FM	[30-60]	256.3	10.7	31.0
FH	[60-80]	243.6	10.1	29.5
FVH	[80-90]	100.0	4.2	12.1
BL	[0-30]	0.5	0.0	0.1
BM	[30-60]	0.1	0.0	0.0
BH	[60-80]	< 0.05	0.0	0.0
BVH	[80-90]	< 0.05	0.0	0.0
UL	[90-100]	74.5	3.1	9.0
UH	[100-180]	127.3	5.3	15.4
Total		825.6	34.4	100.0
BUG Rating		B0-U3-G1		

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

# ZOID

## ZOID BOLLARD

### BOLLARDS



LAST UPDATE: 22-02-2024

#### Accessories



Ordering Code:

AUN-ACB-0011-00

Anchor Bolt Kit for Bollard

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th