CAP

MEDIUM CAP 180


BOLLARD



LAST UPDATE: 21-10-2025



The CAP range is a fresh range of bollards and low mounted pole lights. Designed from scratch with the latest lighting requirements in mind. The highly efficient LEDs are shielded and emit no upward light. The light engine features great color consistency, excellent color rendering index and dimming options. Specification grade optics make the medium sized version a highly competitive lighting tool for demanding professional lighting tasks. With its compact dimensions the small sized CAP is a smart solution for residential lighting projects. Regardless of size the prewired supply cable, numerous mounting solutions and minimized amount of screws assure a simplified installation process.



Technical Data



Ordering Code: 7880-I-A-867-XX

Lamp: LED

Beam : T2 – Asymmetric Long Side Throw


CCT : 3000 K
Lamp Lumen : 2980 lm
Luminaire Lumen : 1800 lm
Lamp Wattage : 28 W
Luminaire Wattage : 30 W
Efficacy : 60 lm/W
Ambient Temperature : 30°C

Lumen Maintenance L80B10 >108,000 h

Controller : CASAMBI

Input Voltage: 220–240Vac 50/60Hz

Net Weight : - kg.





Icon definition



MEDIUM CAP 180

BOLLARD

LAST UPDATE: 21-10-2025



Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP66 Class I

Protection against mechanical impact IK10 on body and IK08 on optical part. IK Rating

High-pressure die cast aluminum alloy body and components. Luminaires Body Housing

Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated **Coating Process**

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C.

Molded PC lens from renowned manufacturers in various light distribution patterns. Lens

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Cable entry protected by M16 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 5-10mm. diameter. Cable Entry

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

High quality CASAMBI controllable LED driver with constant current output. Conform to applicable safety standards and Driver

electromagnetic compatibility.

Enhanced Protection The luminaire is equipped with a 10kV surge protection device, the function of the protector is indicated by a LED, performance in

compliance with IEC61643-11.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Pre-Wire Cable Pre-wired with 3x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.

Equipped with anti-humidity kit.

Caution Installation work has to be carried on according to the enclosed installation manual.


The water drainage system must be tested to ensure that it is working sufficiency and efficiency.


Color



Graphite 02 Dark Grey 03 Aluminum Silver 04

Light Distribution








MEDIUM CAP 180

BOLLARD



LAST UPDATE: 21-10-2025

Bug Report



Lum. Classification System (LCS)				
LCS	Zone	%Lumens	%Lamp	%Lum
FL	[0-30]	167.0	5.6	9.3
FM	[30-60]	580.7	19.5	32.3
FH	[60-80]	148.6	5.0	8.3
FVH	[80-90]	2.9	0.1	0.2
BL	[0-30]	167.0	5.6	9.3
ВМ	[30-60]	580.7	19.5	32.3
ВН	[60-80]	148.6	5.0	8.3
BVH	[80-90]	2.9	0.1	0.2
UL	[90-100]	0.4	0.0	0.0
UH	[100-180]	1.3	0.0	0.1
Total		1800.1	60.4	100.0
BUG Ratir	ng	B1-U1-G1		

CAP

MEDIUM CAP 180

BOLLARD

LAST UPDATE: 21-10-2025



Accessories



Ordering Code: AUN-CON-0009-00 IP68 connection device, cable diameter 5-9.5mm, On-Off



Ordering Code: AUN-CON-0013-00 IP68 connection device, cable diameter 7-11.5mm, On-Off



Ordering Code: AUN-ACB-0003-00 Anchor bolt kit, bollard



Ordering Code: AUN-POL-OO31-XX Aluminum bollard tube, diameter 76mm, H= 833mm, with internal anchorage unit



Ordering Code:
AUN-POL-0032-XX
Aluminum bollard tube,
diameter 76mm, H=
833mm, with flange base



Ordering Code: AUN-POL-0033-XX Aluminum bollard tube, diameter 76mm, H= 2500mm



Ordering Code: AUN-ACB-0020-00 Anchor bolt kit, bollard



Ordering Code: AUN-ACB-0021-00 Anchor bolt, M8x100, expansion type



Ordering Code: AUN-ACB-0013-00 Anchor bolt kit