#### ALESSA 500 - CV


LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025



Alessa is a small sized low voltage supplied range of LED wall washer. Installation on site is simplified by using splash proof in and out connection cables. The adjustable mounting brackets allow fine tuning of the light direction. The small overall dimension allows unobtrusive installation on many different surfaces including niches. The RGBW version is controllable utilizing DMX-RDM and the monochromatic version is optionally controllable with a DALI system. The housing is made of high-corrosion resistant aluminum with low copper content. High ambient temperature rating and high resistance against water ingress make Alessa useable in many countries and applications.



#### Technical Data



Ordering Code : 8018-C-2-011-A2

Lamp: LED

Beam: 45°

CCT: RGBW

Luminaire Lumen: 500 lm

Luminaire Wattage: 12 W

Efficacy: 41 lm/W

Ambient Temperature: 50°C

Lumen Maintenance L70 >36,000 h [@25°C]

Controller : Remote
Input Voltage : 24Vdc
Net Weight : 2.50 kg.

Ordering code guide

B D |

XXXX-X-X-XXXX-XX

A C E

A Product Code
B Reflector
C Electrical Component
D Lamp
E Color



Icon definition

online@unilamp.co.th

www.unilamp.co.th

#### ALESSA 500 - CV

### LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025

#### Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP66 Class III

IK Rating Protection against mechanical impact IKO4

Luminaires Body Housing Extruded Aluminum S6063 alloy body with low copper content.

Coating Process Aluminum anodizing in which aluminum products surface are coated using a wear-resistant oxide layer.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no

accumulation of dust and water.

Lens Molded PMMA lens from renowned manufacturers in various light distribution patterns.

Adjustable Optic Wall mount with adjustable arms.

Gasket Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.

External Screws External screws are in stainless steel with protection grease.

Cable Entry Cable entry protected by M2O cable gland. To be used with HO5RN-F/ HO7RN-F cable with 7-13mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver Driver is not included and has to be ordered separately.

Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.


Pre-Wire Cable Pre-wired with short in and out 2x1 sqmm + 3x0.5 sqmm cable.


Connection provided with IP67 watertight connecting device.

Caution Installation work has to be carried on according to the enclosed installation manual.

Color Graphite A2

#### Light Distribution






ALESSA 500 - CV

LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025

### **Bug Report**



Lum. Classification System (LCS)				
LCS	Zone	%Lumens	%Lamp	%Lum
FL	[0-30]	0.3	0.1	0.1
FM	[30-60]	0.1	0.0	0.0
FH	[60-80]	0.1	0.0	0.0
FVH	[80-90]	< 0.05	0.0	0.0
BL	[0-30]	0.3	0.1	0.1
ВМ	[30-60]	0.1	0.0	0.0
BH	[60-80]	0.1	0.0	0.0
BVH	[80-90]	< 0.05	0.0	0.0
UL	[90-100]	0.2	0.0	0.0
UH	[100-180]	498.8	99.8	99.8
Total		500.0	100.0	100.0
BUG Rating		BO-U3-G0		

online@unilamp.co.th

www.unilamp.co.th

#### ALESSA 500 - CV

### LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025


#### Accessories




Ordering Code:
AUN-CON-0009-00
IP68 connection device,
cable diameter 5-9.5mm,
On-Off



Ordering Code:
AUN-CON-0010-00
IP68 connection device 3
pole, cable diameter
5-9.5mm, with distribution
block



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 150W



Ordering Code: AUN-DRG-0024-00 LED constant voltage driver, 24VDC, 200W




Ordering Code: ATR-CAB-OOO4-OO Feed in cable 2x1sqmm and 3x0.5 sqmm, L= 1000mm, for RGBW luminaire



Ordering Code:
ATR-CAB-0005-00
Jumper cable 2x1sqmm
and 2x1sqmm and 3x0.5,
L= 1000mm, for RGBW
luminaire, for longer
distance between two
luminaires



Ordering Code: ATR-CON-0001-00 Connector end cap



Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W



Ordering Code:
AUN-DMX-0023-00
DMX controller,
Touchscreen



Ordering Code:
AUN-DMX-0024-00
DMX controller, 1-Channel



Ordering Code:
AUN-DMX-0025-00
DMX controller, 2-Channel



Ordering Code: AUN-DMX-0026-00 DMX Connector, 3 pin male, L= 1000mm

### ALESSA 500 - CV

### LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 17-11-2025



Ordering Code: AUN-DMX-0027-01 Splitter, IP67 aluminum enclosure, DMX



Ordering Code: AUN-CON-0022-00 IP67 connection device, cable diameter 4.5-11mm, DMX



Ordering Code: AUN-CON-0023-00 IP67 connection device, cable diameter 4.5-11mm, distribution block , DMX



Ordering Code: ATR-CAB-0006-00 Cable signal, L= 2000mm, DMX



Ordering Code: AUN-CAB-0040-00 Cable H07RN-F 2x1sqmm, L= 2000mm



Ordering Code: AUN-CAB-0039-00 Cable H07RN-F 3x1sqmm, L= 2000mm



Ordering Code: AUN-GSH-0045-01 Glare shield visor