

ALESSA

ALESSA 1000 – CV


LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 21-07-2025



Alessa is a small sized low voltage supplied range of LED wall washer. Installation on site is simplified by using splash proof in and out connection cables. The adjustable mounting brackets allow fine tuning of the light direction. The small overall dimension allows unobtrusive installation on many different surfaces including niches. The RGBW version is controllable utilizing DMX-RDM and the monochromatic version is optionally controllable with a DALI system. The housing is made of high-corrosion resistant aluminum with low copper content. High ambient temperature rating and high resistance against water ingress make Alessa useable in many countries and applications.



Technical Data



Ordering Code :	8019-H-2-003-A2
Lamp :	LED
Beam :	50°/20°
CCT :	3000 K
CRI :	CRI >80
SDCM :	SDCM = 5
Luminaire Lumen :	1936 lm
Luminaire Wattage :	24 W
Efficacy :	80 lm/W
Ambient Temperature :	50°C
Lumen Maintenance	L90 >60,500 h (@25°C)
Controller :	Remote
Input Voltage :	24Vdc
Net Weight :	4.50 kg.

Ordering code guide

XXXX-X-X-XXX-XX				
A	B	C	D	E
Product Code	Reflector	Electrical Component	Lamp	Color



Icon definition

*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.


Unilamp Co., Ltd.
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1
Fax : +66(0)2 943 2419
online@unilamp.co.th
www.unilamp.co.th

ALESSA 1000 – CV



LINEAR LIGHT | WALL SURFACE LIGHT

LAST UPDATE: 21-07-2025

Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP66 Class III
IK Rating	Protection against mechanical impact IK04
Luminaires Body Housing	Extruded Aluminum 6063 alloy body with low copper content.
Coating Process	Aluminum anodizing in which aluminum products surface are coated using a wear-resistant oxide layer.
Diffuser	Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no accumulation of dust and water.
Lens	Molded PMMA lens from renowned manufacturers in various light distribution patterns.
Adjustable Optic	Wall mount with adjustable arms.
Gasket	Post-cured treated silicone gasket. Temperature and weather resistant. Working temperature -40°C to +200°C.
External Screws	External screws are in stainless steel with protection grease.
Cable Entry	Cable entry protected by M20 cable gland. To be used with H05RN-F/ H07RN-F cable with 7-13mm. diameter.
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.
Driver	Driver is not included and has to be ordered separately.
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Pre-Wire Cable	Pre-wired with short in and out 2x1 sqmm cable. Connection provided with IP67 watertight connecting device.
Caution	Installation work has to be carried on according to the enclosed installation manual.
Color	 Graphite A2

Light Distribution



ALESSA


ALESSA 1000 – CV

LINEAR LIGHT | WALL SURFACE LIGHT



LAST UPDATE: 21-07-2025


Bug Report




Lum. Classification System (LCS)				
LCS	Zone	%Lumens	%Lamp	%Lum
FL	[0-30]	1.4	0.1	0.1
FM	[30-60]	0.4	0.0	0.0
FH	[60-80]	< 0.05	0.0	0.0
FVH	[80-90]	0.0	0.0	0.0
BL	[0-30]	1.4	0.1	0.1
BM	[30-60]	0.4	0.0	0.0
BH	[60-80]	< 0.05	0.0	0.0
BVH	[80-90]	0.0	0.0	0.0
UL	[90-100]	0.4	0.0	0.0
UH	[100-180]	1919.6	98.9	99.8
Total		1923.6	99.1	100.0
BUG Rating		B0-U5-G0		

*Due to the constancy of product development,
we reserve the right to alter all specification
without prior notice.

Accessories




Ordering Code:
AUN-DRG-0011-00
LED constant voltage
driver, 24VDC, 150W



Ordering Code:
AUN-DRG-0024-00
LED constant voltage
driver, 24VDC, 200W




Ordering Code:
ATR-CAB-0002-00
Feed in cable 2x1sqmm, L=
1000mm, for
monochromatic luminaire



Ordering Code:
ATR-CAB-0003-00
Jumper cable 2x1sqmm, L=
1000mm, for
monochromatic luminaire,
for longer distance
between two luminaires




Ordering Code:
ATR-CON-0001-00
Connector end cap




Ordering Code:
AUN-DRG-0027-00
LED constant voltage
driver, 24VDC, 72W



Ordering Code:
AUN-GSH-0046-01
Glare shield visor



Ordering Code:
AUN-DRG-0100-00
LED constant voltage
driver, 24VDC, 60W, DALI



Ordering Code:
AUN-DRG-0101-00
LED constant voltage
driver, 24VDC, 120W, DALI