LUXBEAT

LUXBEAT

ACCENT LINEAR LIGHT




LAST UPDATE: 19-04-2024



LuxBeat and LuxBeat XL are a range of miniature sized linear accent luminaires with flexible and fixed application. The patented optical system emits homogenous light regardless of the viewing direction. LuxBeat is the designer's choice for unconstraint creative light installations. High contrasting illumination of building elements is easily possible with the tiny luminaire dimensions and state of the art LED performance. The luminaire is top bendable and can be shortened on–site. The use of optional stainless steel mounting clips eliminates the time–consuming pretreatment of the installation surface. LuxBeat XL offers a robust aluminum housing that contains a wiring channel for the electrical connection. Bottom mounted in and out connector's assure shadow free easy installation. LuxBeat XL is available as fixed and tiltable surface mount luminaire, recessed wall and ceiling light, pendant light and inground uplighter. Shorter luminaire lengths are available upon request. LuxBeat XL RGBW requires the use of a 4 channel CV RGBW controller, contact the Unilamp sales team for details.

L70B10 >50,000 h



Technical Data



Ordering Code : 8101-0-2-467-00

Lamp: LED Beam: 120° CCT: 3000 K CRI: CRI >80 SDCM: SDCM = 3Luminaire Lumen: 680 lm/M Luminaire Wattage: 7 W/M Efficacy: 97 lm/W/M

Ambient Temperature : 50°C

Lumen Maintenance

Controller : Remote
Input Voltage : 24Vdc
Net Weight : - kg.



Icon definition

LUXBEAT

LUXBEAT

ACCENT LINEAR LIGHT



LAST UPDATE: 19-04-2024

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-1 Fixed Luminaires

Protection IP67 Class III

Luminaires Body Housing High quality silicone extrusion housing.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on FPC.

Driver Driver is not included and has to be ordered separately.


Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.


Pre-Wire Cable Pre-wired cable 2x0.5sqmm, L=300mm

Caution Installation, dismantling and repairs must be carried out by qualified electrician.

Maximum continuous installation length for 1 driver is 5m. Custom length is available (prepared by the factory).

Light Distribution





LUXBEAT


LUXBEAT

ACCENT LINEAR LIGHT



LAST UPDATE: 19-04-2024


Accessories




Ordering Code: AUN-DRG-0011-00 LED Constant Voltage Driver 24Vdc 150W.



Ordering Code: AUN-CAB-0006-00 Power cable kit: 300mm cable with endcap + front cap



Ordering Code: AUN-DRG-0022-00 LED Constant Voltage Driver 24Vdc 60W. [DALI]



Ordering Code: AUN-DRG-0023-00 LED Constant Voltage Driver 24Vdc 12OW. [DALI]



Ordering Code: AUN-CON-0024-00 Gel-Filled IP68 Connector Cable Diameter 4.8 - 6mm.



Ordering Code: AUN-DRG-0024-00 LED Constant Voltage Driver 24Vdc 200W.



Ordering Code: AUN-DRG-0025-00 LED Constant Voltage Driver 24Vdc 200W. [DALI]



Ordering Code: AUN-DRG-0027-00 LED Constant Voltage Driver 24Vdc 72W.



Ordering Code: AUN-BRK-0009-00 Mounting clip, set of 20pcs