





LuxBeat, LuxBeat L, LuxBeat XL, LuxBeat Inground, and LuxBeat Underwater are miniature linear accent luminaires for both flexible and fixed applications. With a patented optical system, they deliver uniform light output from every angle, creating precise, high-contrast illumination of architectural features. Their compact size enables accurate highlighting and versatile installation. LuxBeat is top bendable and can be shortened on-site to meet project requirements. Stainless steel clips allow direct mounting to walls or fâades without surface cleaning or pretreatment, simplifying installation. LuxBeat L features an aluminum housing for fixed use or clips for flexible mounting, ensuring smooth, shadow-free connections. Its slim design produces sharp, elegant lighting that highlights architectural details. LuxBeat XL offers a robust aluminum housing with an integrated wiring channel and bottom connectors for seamless installation. It is available as fixed or tiltable surface luminaires, recessed wall and ceiling lights, and pendants, with custom lengths on request. LuxBeat Inground provides a recessed solution for concrete floors and outdoor grounds, delivering durability and the same optical performance as the rest of the family. LuxBeat Underwater extends this reliability into pools, fountains, and water features. For RGBW color projects, contact the Unilamp sales team.



#### Ordering code guide



#### Technical Data



Ordering Code :	8111-0-2-269-00
Lamp :	LED
Beam :	120°
CCT :	3000 K
CRI :	CRI >80
SDCM :	SDCM = 3
Luminaire Lumen :	440 lm
Luminaire Wattage :	9 W
Efficacy :	48 lm/W/M
Ambient Temperature :	45°C
Lumen Maintenance	L80B10 >60,000 h
Controller :	Remote
Input Voltage :	24Vdc
Net Weight :	- kg.





Icon definition


#### Specification

IEC Standard	IEC 60598-1 General Requirement
	IEC 60598-2-1 Fixed Luminaires
Protection	IP67 Class III
Luminaires Body Housing	Advanced co-extruded silicone housing offering superior flexibility and longevity. Dual-bend structure supports both top-bend and side-bend applications. Bottom feed connection allows hidden wiring integration. Factory cutting available at fixed 62.5 mm steps.
Cable Entry	Electrical loop in and out, with M12 connector
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on FPC.
Driver	Driver is not included and has to be ordered separately.
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Pre-Wire Cable	Pre-wired cable 2x0.75sqmm, L=150mm
Caution	Installation, maintenance, and repairs should only be performed by a certified electrician. The maximum continuous installation length per driver is 5 meters. Custom lengths can be prepared upon request by the factory.


#### Light Distribution




#### Accessories



Ordering Code:  
AUN-DRG-0011-00  
LED constant voltage  
driver, 24VDC, 150W



Ordering Code:  
AUN-DRG-0024-00  
LED constant voltage  
driver, 24VDC, 200W



Ordering Code:  
AUN-DRG-0025-00  
LED constant voltage  
driver, 24VDC, 200W, DALI



Ordering Code:  
AUN-MOT-0014-XX  
Surface mount profile, L=  
510mm




Ordering Code:  
AUN-CON-0015-00  
Feed in cable 2x0.75sqmm,  
L= 2000mm, for  
monochromatic luminaire ,  
with M12 connector




Ordering Code:  
ATR-MOT-0001-00  
Suspension kit, with  
mounting loop



Ordering Code:  
ATR-MOT-0002-00  
Suspension kit, with  
mounting post



Ordering Code:  
AUN-DRG-0027-00  
LED constant voltage  
driver, 24VDC, 72W




Ordering Code:  
AUN-RCH-0013-XX  
Recessed ceiling mounting  
profile, L= 546mm



Ordering Code:  
AUN-MOT-0026-XX  
Plasterboard wall mounting  
profile, L= 546mm



Ordering Code:  
AUN-MOT-0029-XX  
Wall niche mounting  
profile, L= 546mm



Ordering Code:  
AUN-BRK-0007-XX  
Mounting bracket,  
adjustable


# LUXBEAT

## LUXBEAT XL 500


### LINEAR LIGHT

 **Unilamp**


LAST UPDATE: 11-02-2026



**Ordering Code:**  
AUN-DRG-0124-00  
**LED constant voltage**  
driver, 24VDC, 120W,  
DIM0/1-10V



**Ordering Code:**  
AUN-DRG-0100-00  
**LED constant voltage**  
driver, 24VDC, 60W, DALI



**Ordering Code:**  
AUN-DRG-0101-00  
**LED constant voltage**  
driver, 24VDC, 120W, DALI