

# LUXBEAT

## LUXBEAT XL 1000


### ACCENT LINEAR LIGHT



LAST UPDATE: 07-05-2024



LuxBeat and LuxBeat XL are a range of miniature sized linear accent luminaires with flexible and fixed application. The patented optical system emits homogenous light regardless of the viewing direction. LuxBeat is the designer's choice for unconstrained creative light installations. High contrasting illumination of building elements is easily possible with the tiny luminaire dimensions and state of the art LED performance. The luminaire is top bendable and can be shortened on-site. The use of optional stainless steel mounting clips eliminates the time-consuming pretreatment of the installation surface. LuxBeat XL offers a robust aluminum housing that contains a wiring channel for the electrical connection. Bottom mounted in and out connector's assure shadow free easy installation. LuxBeat XL is available as fixed and tiltable surface mount luminaire, recessed wall and ceiling light, pendant light and inground uplighter. Shorter luminaire lengths are available upon request. LuxBeat XL RGBW requires the use of a 4 channel CV RGBW controller, contact the Unilamp sales team for details.



## Technical Data



Ordering Code :	8112-O-2-269-00
Lamp :	LED
Beam :	120°
CCT :	3000 K
CRI :	CRI >80
SDCM :	SDCM = 3
Luminaire Lumen :	880 lm
Luminaire Wattage :	18 W
Efficacy :	48 lm/W
Ambient Temperature :	45°C
Lumen Maintenance	L80B10 >60,000 h
Controller :	Remote
Input Voltage :	24Vdc
Net Weight :	- kg.

### Ordering code guide

XXXX-X-X-XXX-XX				
A	B	C	D	E
Product Code	Reflector	Electrical Component	Lamp	Color



Icon definition

\*Due to the constancy of product development, we reserve the right to alter all specification without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66(0)2 943 2420-1, +66(0)2 946 4170-1  
Fax : +66(0)2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th

# LUXBEAT

## LUXBEAT XL 1000

### ACCENT LINEAR LIGHT





LAST UPDATE: 07-05-2024

#### Specification

IEC Standard	IEC 60598-1 General Requirement IEC 60598-2-1 Fixed Luminaires
Protection	IP67 Class III
Luminaires Body Housing	Co-extruded silicone housing
Cable Entry	Electrical loop in and out, with M12 connector
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on FPC.
Driver	Driver is not included and has to be ordered separately.
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Pre-Wire Cable	Pre-wired cable 2x0.75sqmm, L=150mm
Caution	Installation, dismantling and repairs must be carried out by qualified electrician. Maximum continuous installation length for 1 driver is 5m. Custom length is available [prepared by the factory].

#### Light Distribution




\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th


#### Accessories




Ordering Code:  
AUN-DRG-0011-00  
LED Constant Voltage  
Driver 24Vdc 150W.




Ordering Code:  
AUN-DRG-0022-00  
LED Constant Voltage  
Driver 24Vdc 60W. [DALI]




Ordering Code:  
AUN-DRG-0023-00  
LED Constant Voltage  
Driver 24Vdc 120W. [DALI]



Ordering Code:  
AUN-DRG-0024-00  
LED Constant Voltage  
Driver 24Vdc 200W.



Ordering Code:  
AUN-DRG-0025-00  
LED Constant Voltage  
Driver 24Vdc 200W. [DALI]



Ordering Code:  
AUN-MOT-0015-XX  
Surface Mount Aluminium  
Profile L = 1010mm.




Ordering Code:  
AUN-CON-0015-00  
Input Cable L=2000mm  
One-Side with M12 Female  
Connector.




Ordering Code:  
ATR-MOT-0001-00  
Suspension Kit with  
Mounting Loop.



Ordering Code:  
ATR-MOT-0002-00  
Suspension Kit with  
Mounting Post.



Ordering Code:  
AUN-DRG-0027-00  
LED Constant Voltage  
Driver 24Vdc 72W.



Ordering Code:  
AUN-RCH-0014-XX  
Mounting Profile for  
Recessed Ceiling L =  
1046mm.



Ordering Code:  
AUN-MOT-0027-XX  
Mounting Profile for  
Plasterboard Wall L =  
1046mm.

# LUXBEAT

LUXBEAT XL 1000

ACCENT LINEAR LIGHT



LAST UPDATE: 07-05-2024



Ordering Code:  
AUN-MOT-0030-XX  
Mounting Profile for Wall  
Niche L = 1046mm.



Ordering Code:  
AUN-BRK-0007-XX  
Adjustable Bracket.

\*Due to the constancy of product development,  
we reserve the right to alter all specification  
without prior notice.

Unilamp Co., Ltd.  
461 Ramintra Road, Kannayao, Bangkok 10230 Thailand  
Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1  
Fax : +66[0]2 943 2419  
online@unilamp.co.th  
www.unilamp.co.th