




LuxBeat, LuxBeat L, LuxBeat XL, LuxBeat Inground, and LuxBeat Underwater are miniature linear accent luminaires for both flexible and fixed applications. With a patented optical system, they deliver uniform light output from every angle, creating precise, high-contrast illumination of architectural features. Their compact size enables accurate highlighting and versatile installation. LuxBeat is top bendable and can be shortened on-site to meet project requirements. Stainless steel clips allow direct mounting to walls or fâades without surface cleaning or pretreatment, simplifying installation. LuxBeat L features an aluminum housing for fixed use or clips for flexible mounting, ensuring smooth, shadow-free connections. Its slim design produces sharp, elegant lighting that highlights architectural details. LuxBeat XL offers a robust aluminum housing with an integrated wiring channel and bottom connectors for seamless installation. It is available as fixed or tiltable surface luminaires, recessed wall and ceiling lights, and pendants, with custom lengths on request. LuxBeat Inground provides a recessed solution for concrete floors and outdoor grounds, delivering durability and the same optical performance as the rest of the family. LuxBeat Underwater extends this reliability into pools, fountains, and water features. For RGBW color projects, contact the Unilamp sales team.



#### Ordering code guide

XXXX-X-X-XXX-XX

A      B      C      D      E

- A Product Code
- B Reflector
- C Electrical Component
- D Lamp
- E Color

#### Technical Data



Ordering Code : 8112-0-2-399-00

Lamp : LED

Beam : 120°

CCT : RGBW

Luminaire Lumen : 430 lm

Luminaire Wattage : 18 W

Efficacy : 23 lm/W

Ambient Temperature : 45°C

Lumen Maintenance L80B10 >60,000 h

Controller : Remote

Input Voltage : 24Vdc

Net Weight : - kg.





Icon definition


#### Specification

IEC Standard	IEC 60598-1 General Requirement
	IEC 60598-2-1 Fixed Luminaires
Protection	IP67 Class III
Luminaires Body Housing	Advanced co-extruded silicone housing offering superior flexibility and longevity.
Cable Entry	Electrical loop in and out, with M12 connector
Led	High efficiency LED module utilized chips from world renowned manufacturer. Assembled on FPC.
Driver	Requires the use of a 4 channel CV RGBW controller
Internal Wire	Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.
Pre-Wire Cable	Pre-wired cable 5x0.75sqmm, L=150mm
Caution	Installation, maintenance, and repairs should only be performed by a certified electrician.
	The maximum continuous installation length per driver is 5 meters. Custom lengths can be prepared upon request by the factory.


#### Light Distribution



#### Accessories



Ordering Code:  
AUN-DRG-0011-00  
LED constant voltage  
driver, 24VDC, 150W



Ordering Code:  
AUN-DRG-0024-00  
LED constant voltage  
driver, 24VDC, 200W




Ordering Code:  
AUN-MOT-0015-XX  
Surface mount profile, L= 1010mm



Ordering Code:  
ATR-MOT-0001-00  
Suspension kit, with  
mounting loop



Ordering Code:  
ATR-MOT-0002-00  
Suspension kit, with  
mounting post



Ordering Code:  
AUN-DRG-0027-00  
LED constant voltage  
driver, 24VDC, 72W



Ordering Code:  
AUN-RCH-0014-XX  
Recessed ceiling mounting  
profile, L= 1046mm




Ordering Code:  
AUN-MOT-0027-XX  
Plasterboard wall mounting  
profile, L= 1046mm



Ordering Code:  
AUN-MOT-0030-XX  
Wall niche mounting  
profile, L= 1046mm



Ordering Code:  
ATR-CON-0002-00  
Feed in cable 5x0.75sqmm,  
L= 2000mm, for RGBW  
luminaire, with M12  
connector



Ordering Code:  
AUN-BRK-0007-XX  
Mounting bracket,  
adjustable



Ordering Code:  
AUN-DRG-0119-00  
LED constant voltage  
decoder, 24Vdc, 180W,  
with IP67 GFR polymer  
enclosure, DMX512/RDM

# LUXBEAT

## LUXBEAT XL 1000

### LINEAR LIGHT

 **Unilamp**


LAST UPDATE: 06-01-2026




Ordering Code:  
AUN-CON-0010-00  
IP68 connection device 3  
pole, cable diameter  
5-9.5mm, with distribution  
block




Ordering Code:  
AUN-CON-0009-00  
IP68 connection device,  
cable diameter 5-9.5mm,  
On-Off



Ordering Code:  
AUN-CAB-0039-00  
Cable HO7RN-F 3x1sqmm,  
L= 2000mm



Ordering Code:  
AUN-CAB-0040-00  
Cable HO7RN-F 2x1sqmm,  
L= 2000mm



Ordering Code:  
ATR-CAB-0006-00  
Cable signal, L= 2000mm,  
DMX



Ordering Code:  
AUN-CON-0023-00  
IP67 connection device,  
cable diameter 4.5-11mm,  
distribution block , DMX



Ordering Code:  
AUN-CON-0022-00  
IP67 connection device,  
cable diameter 4.5-11mm,  
DMX



Ordering Code:  
AUN-DMX-0027-01  
Splitter, IP67 aluminum  
enclosure, DMX




Ordering Code:  
AUN-DMX-0026-00  
DMX Connector, 3 pin  
male, L= 1000mm



Ordering Code:  
AUN-DMX-0025-00  
DMX controller, 2-Channel



Ordering Code:  
AUN-DMX-0024-00  
DMX controller, 1-Channel



Ordering Code:  
AUN-DMX-0023-00  
DMX controller,  
Touchscreen