




ZET walk-over in ground uplighter with fixed and adjustable optic utilized high-performance LED with additional glare control accessory to deliver the best and comfortable light distribution. ZET Adjustable is available in COB LED or High Power LED with various beam angle option. It is supplied with a post-cured silicone gasket with pre-wire cable for outdoor use. ZET is commonly used to highlight architectural tasks, wall structures, low ceilings, and columns. The glare-shield honey comb and softening lens are available as accessories. A gel-filled IP68 connection device for water tight connection is also available as standard option. Retrofit solution with GU5.3 or GU10 Led lamp base is presented in this family. The installation of this product and drainage system must be done according to the product's manual.



## Technical Data



|                       |                                |
|-----------------------|--------------------------------|
| Ordering Code :       | 9002-0-2-920-91                |
| Lamp :                | LED                            |
| CCT :                 | 4000 K                         |
| CRI :                 | CRI >80                        |
| SDCM :                | SDCM = 3                       |
| Lamp Lumen :          | 1010 lm                        |
| Luminaire Lumen :     | 540 lm                         |
| Lamp Wattage :        | 8.6 W(350mA)                   |
| Luminaire Wattage :   | 8.6 W                          |
| Efficacy :            | 62 lm/W                        |
| Ambient Temperature : | 50°C                           |
| Lumen Maintenance     | L70B10 >60,000 h               |
| Controller :          | Remote                         |
| Input Voltage :       | 350mA, 24.5Vdc, Uin max 150Vdc |
| Net Weight :          | 1.10 kg.                       |

## Ordering code guide

XXXX-X-X-XXX-XX

- A Product Code  
B Reflector  
C Electrical Component  
D Lamp  
E Color





### Icon definition

### Specification

|                         |   |
|-------------------------|---|
| IEC Standard            | IEC 60598-1 General Requirement<br>IEC 60598-2-13 Ground Recessed Luminaires  |
| Protection              | IP67 Class III  |
| IK Rating               | Protection against mechanical impact IK10 on body and IK08 on optical part.   |
| Luminaires Body Housing | High-pressure die cast aluminum alloy body and components.<br>Front cover in 316 stainless steel brush finished.<br>Recessed housing made of GFR polymer.<br>Luminaire withstands a maximum static load of 1000 kg.               |
| Coating Process         | Nano Ceramic surface conversion, resistant to corrosive environment. Luminaire primarily coated with epoxy resin and top coated with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C. |
| Diffuser                | Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no accumulation of dust and water.   |
| Gasket                  | Weather resistant silicone gasket. Working temperature -40°C to +200°C.   |
| External Screws         | Marine grade 316 stainless steel screw.   |
| Cable Entry             | Cable entry protected by M16 cable gland. To be used with H05RN-F/ H07RN-F cable with 5-10mm. diameter.   |
| Led                     | High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat conductive material.  |
| Driver                  | Driver is not included and has to be ordered separately.  |
| Pre-Wire Cable          | Pre-wired with 2x1.0 sqmm. H07RN-F neoprene cable. IMQ approved.  |
| Caution                 | Installation work has to be carried on according to the enclosed installation manual.<br>The water drainage system must be tested to ensure that it is working sufficiency and efficiency.  |

### Light Distribution



### Accessories



Ordering Code:  
AUN-DRG-0003-01  
LED constant current  
driver, 350mA, 15W, with  
IP67 GFR polymer  
enclosure, On-Off



Ordering Code:  
AUN-CON-0013-00  
IP68 connection device,  
cable diameter 7-11.5mm,  
On-Off



Ordering Code:  
AUN-RCH-0005-00  
Recessed installation  
housing



Ordering Code:  
AUN-CON-0007-00  
IP68 distribution box,  
series wiring, for 1-3  
luminaires



Ordering Code:  
AUN-CON-0004-00  
IP68 Connector, cable  
diameter 8-10mm,  
gel-filled