ZET

ZET ROUND OPAL - CVDA


INGROUND LIGHT







ZET walk-over in ground uplighter with fixed and adjustable optic utilized high-performance LED with additional glare control accessory to deliver the best and comfortable light distribution. ZET Adjustable is available in COB LED or High Power LED with various beam angle option. It is supplied with a post-cured silicone gasket with pre-wire cable for outdoor use. ZET is commonly used to highlight architectural tasks, wall structures, low ceilings, and columns. The glare-shield honey comb and softening lens are available as accessories. A gel-filled IP68 connection device for water tight connection is also available as standard option. Retrofit solution with GU5.3 or GU10 Led lamp base is presented in this family. The installation of this product and drainage system must be done according to the product's manual.



CRI : SDCM : Lamp Lumer Luminaire Lu Lamp Watta Ordering code guide

XXXX—X—XXX—XX

A C E

A Product Code
B Reflector
C Electrical Component
D Lamp
F Color



Icon definition

Technical Data



Ordering Code : 9002-0-7-585-91

Lamp: LED CCT: 4000 K CRI >80 SDCM = 3Lamp Lumen: 1440 lm Luminaire Lumen : 330 lm Lamp Wattage: 13 W(24Vdc) Luminaire Wattage: 13 W Efficacy: 25 lm/W Ambient Temperature : 50°C

Lumen Maintenance L70B10 >66,000 h
Controller: On-Off / DALI

Input Voltage : 24Vdc Net Weight : 1.20 kg.



ZET ROUND OPAL - CVDA

INGROUND LIGHT



LAST UPDATE: 16-10-2025

Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-13 Ground Recessed Luminaires

Protection IP67 Class I

Protection against mechanical impact IK10 on body and IK08 on optical part. IK Rating

High-pressure die cast aluminum alloy body and components. Luminaires Body Housing

Front cover in 316 stainless steel brush finished.

Recessed housing made of GFR polymer.

Luminaire withstands a maximum static load of 1000 kg.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no

accumulation of dust and water.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns. Gasket

Weather resistant silicone gasket. Working temperature -40°C to +200°C.

Marine grade 316 stainless steel screw. External Screws

Cable Entry Cable entry protected by M16 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 5-10mm. diameter.

High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat Led

conductive material.


Driver Driver is not included and has to be ordered separately.


Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.

Pre-Wire Cable Pre-wired with 5-core cable for power (3x1 sqmm.) and dimming signal (2x0.35 sqmm.). Installation work has to be carried on according to the enclosed installation manual. Caution

The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light Distribution





ZET


ZET ROUND OPAL - CVDA

INGROUND LIGHT

⊉Unilamp

LAST UPDATE: 16-10-2025


Accessories



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 15OW



Ordering Code: AUN-CON-0014-00 IP68 connection device, cable diameter 8-12.5mm, 1-10V or DALI



Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W