ZET

ZET ROUND ADJUSTABLE - CV


INGROUND LIGHT

LAST UPDATE: 07-11-2025





ZET walk-over in ground uplighter with fixed and adjustable optic utilized high-performance LED with additional glare control accessory to deliver the best and comfortable light distribution. ZET Adjustable is available in COB LED or High Power LED with various beam angle option. It is supplied with a post-cured silicone gasket with pre-wire cable for outdoor use. ZET is commonly used to highlight architectural tasks, wall structures, low ceilings, and columns. The glare-shield honey comb and softening lens are available as accessories. A gel-filled IP68 connection device for water tight connection is also available as standard option. Retrofit solution with GU5.3 or GU10 Led lamp base is presented in this family. The installation of this product and drainage system must be done according to the product's manual.



Technical Data



Ordering Code : 9013-C-2-584-91

Lamp: LED 46° Beam: CCT: 3000 K CRI: CRI >80 SDCM: SDCM = 3Lamp Lumen: 960 lm Luminaire Lumen : 740 lm Lamp Wattage: 8.1 W(24Vdc)

Luminaire Wattage : 8.1 W
Efficacy : 91 lm/W
Ambient Temperature : 40°C

Lumen Maintenance L70B10 >66,000 h

Controller : Remote Input Voltage : 24Vdc
Net Weight : 1.40 kg.

B D |
XXXX-X-X-XXX-XX
A C E

A Product Code
B Reflector
C Electrical Component
D Lamp

Ordering code guide



Color

Icon definition



ZET ROUND ADJUSTABLE - CV

INGROUND LIGHT

LAST UPDATE: 07-11-2025



Specification

IEC Standard IEC 60598-1 General Requirement

IEC 60598-2-13 Ground Recessed Luminaires

Protection IP67 Class III

IK Rating Protection against mechanical impact IK10 on body and optical part.

Luminaires Body Housing High-pressure die cast aluminum alloy body and components.

Front cover in 316 stainless steel brush finished.

Recessed housing made of GFR polymer.

Luminaire withstands a maximum static load of 1000 kg.

Coating Process Nano Ceramic surface conversion, resistant to corrosive environment. Luminiare primarily coated with epoxy resin and top coated

with UV stabilized polyester powder and cured in digital temperature controlled chamber at 200°C.

Diffuser Impact resistant safety tempered glass cover. Able to withstand the temperature up to 250°C. Glass flushes to the front cover, no

accumulation of dust and water.

Lens Molded PC lens from renowned manufacturers in various light distribution patterns.

Adjustable Optic Adjustable optical unit.

Gasket Weather resistant silicone gasket. Working temperature -40°C to +200°C.

External Screws Marine grade 316 stainless steel screw.

Cable Entry Cable entry protected by M16 cable gland. To be used with HO5RN-F/ HO7RN-F cable with 5-10mm. diameter.

Led High efficiency LED module utilized chips from world renowned manufacturer. Assembled on MCPCB and mounted on to heat

conductive material.

Driver Driver is not included and has to be ordered separately.


Internal Wire Tinned copper conductor with silicone insulated internal wire. IMQ approved. Working temperature -40°C to +180°C.


Pre-Wire Cable Pre-wired with 2x1.0 sqmm. HO7RN-F neoprene cable. IMQ approved.

Caution Installation work has to be carried on according to the enclosed installation manual.

The water drainage system must be tested to ensure that it is working sufficiency and efficiency.

Light Distribution





www.unilamp.co.th

ZET

ZET ROUND ADJUSTABLE - CV

INGROUND LIGHT


LAST UPDATE: 07-11-2025




Accessories



Ordering Code:
AUN-GSH-0008-00
Honeycomb louver, LED,
pre-assembly from factory



Ordering Code: AUN-SOF-0022-00 Softening filter, LED, pre-assembly from factory



Ordering Code: AUN-DRG-0011-00 LED constant voltage driver, 24VDC, 150W



Ordering Code: AUN-CON-0013-00 IP68 connection device, cable diameter 7-11.5mm, On-Off




Ordering Code: AUN-CON-0004-00 IP68 Connector, cable diameter 8-10mm, qel-filled



Ordering Code:
AUN-CON-0003-00
IP68 Connector, cable
diameter 8-10mm,
qel-filled for through wiring




Ordering Code: AUN-DRG-0024-00 LED constant voltage driver, 24VDC, 200W




Ordering Code: AUN-DRG-0027-00 LED constant voltage driver, 24VDC, 72W




Ordering Code: AUN-CAB-0040-00 Cable H07RN-F 2x1sqmm, L= 2000mm



Ordering Code: AUN-DRG-0118-00 LED constant voltage driver, 24VDC, 30W



Ordering Code: AUN-DRG-0100-00 LED constant voltage driver, 24VDC, 60W, DALI



Ordering Code: AUN-DRG-0101-00 LED constant voltage driver, 24VDC, 120W, DALI