



NEW FAMILY!

REGOR

■ SURFACE WASHER & FLOOD LIGHT

REGOR

NEW
Release

■ SURFACE WASHER & FLOOD LIGHT



REGOR is robust designed high performing flood light suitable for a wide range of applications. Equipped with a pre-wired cable of 1500mm length for rapid and cost-saving installation. The internal vent prevents moisture buildup and extends the useful life time and reliability. The integrated scale allows easy and reliable aiming. With a range of symmetric and asymmetric beams REGOR is a great choice for car parks, façade lighting and general large scale outdoor lighting applications. With a temperature range from -30°C to 50°C , IP66 water ingress protection and light weight construction REGOR ticks many boxes in everyday lighting specifications.



Specification


- Designed, Manufactured and Tested according to IEC 60598.
- LM6 Die Cast Aluminium body and components.
- Stainless steel screws.
- Luminaire top coated with UV stabilized polyester powder and cured.
- Double layer coating.
- Safety glass cover.
- Molded Lens from renowned manufacturer.
- Post-cured silicone gasket.
- High quality LED module and driver.
- Pre-wired cable from the factory.
- Installation must be carried out according to the enclosed product manual.

Available Color


Black

[replace the last 2 digits of ordering code with A1]


REGOR 100 – Flood light




REGOR 150 – Flood light



REGOR 200 – Flood light



REGOR 300 – Flood light



REGOR

NEW!

SURFACE WASHER & FLOOD LIGHT

REGOR 100 – Flood light / 2201

REGOR 150 – Flood light / 2202

REGOR 200 – Flood light / 2203

REGOR 300 – Flood light / 2204

Luminaire Performance

15270 – 46220 lm

107 – 295 W

142 – 157 lm/W

Beam Options



Color Temperature

5000K

Controller

On-Off

Product Code	Product Name	Luminaire Wattage	Beam	CCT	Luminaire Lumen	Controller
OD-2201 	REGOR 100 – Flood light	107 W	28° 53° T3	5000 K 5000 K 5000 K	16000 lm 16390 lm 15270 lm	On-Off On-Off On-Off
OD-2202 	REGOR 150 – Flood light	153 W	28° 53° T3	5000 K 5000 K 5000 K	22240 lm 22830 lm 21840 lm	On-Off On-Off On-Off
OD-2203 	REGOR 200 – Flood light	190 W	28° 53° T3	5000 K 5000 K 5000 K	28310 lm 29980 lm 28480 lm	On-Off On-Off On-Off
OD-2204 	REGOR 300 – Flood light	295 W	28° 53° T3	5000 K 5000 K 5000 K	45300 lm 46220 lm 43750 lm	On-Off On-Off On-Off

Application Reference



Unilamp Co., Ltd.

461 Ramintra Road, Kannayao, Bangkok 10230 Thailand

Tel : +66[0]2 943 2420-1, +66[0]2 946 4170-1

Fax : +66[0]2 943 2419

unilamp@unilamp.co.th | online@unilamp.co.th



www.unilamp.co.th