

















INSTRUCCIONES DE ENSAMBLAJE / ASSEMBLY INSTRUCTIONS


















1. Strip the cable to a length of 14-15mm. Strip the wire to a length of 7-8mm.
Recommended cable OD: maximum 12.5mm / minimum 6mm.
2. Thread the cable through the cable gland (A), the cable seal (B) and the nut (C).
3. Connect the cable to the terminal block (D). Recommended tightening torque: 0.5Nm
4. Screw the nut (C) to the terminal block (D). Recommended tightening torque: 0.1Nm.
5. Screw the cable gland (A) to the nut (C). Recommended tightening torque: 0.1Nm.

0497-0-9-000-00 IP68 Water Tight Connecting Device, 3 Pole, Cable Diameter 7 - 11.5mm.

PLUG PLUGGABLE CONNECTOR 2 POLES +  70734000_Plug Connector IP 68 2 Pole + PE 0.5-2.5 mm ² WP3/M (TEKOX)			
WP3/M 		 25 pcs. 150x120x110 mm	 0,52 Kg
FLEXIBLE CABLE  14-15 mm 7,8 mm 0,5 -2,5 mm ² Cable seals included Ø8mm, Ø9,5mm Ø11,5mm	 46,5 ⁺² Ø25,5	 -40°C +85°C Voltage/Current rating 450V / 17,5A	
SOCKET PLUGGABLE CONNECTOR 2 POLES +  70735000_Socket Connector IP 68 2 Pole + PE 0.5-2.5 mm ² WP3/H (TEKOX)			
WP3/H 		 25 pcs. 150x120x110 mm	 0,57 Kg
FLEXIBLE CABLE  14-15 mm 7,8 mm 0,5 -2,5 mm ² Cable seals included Ø8mm, Ø9,5mm Ø11,5mm	 50,5 ⁺² Ø25,5	 -40°C +85°C Voltage/Current rating 450V / 17,5A	

0498-0-9-000-00 IP68 Water Tight Connecting Device 5 Pole, Cable Diameter 8 - 12.5mm. (1-10V or DALI)

PLUG PLUGGABLE CONNECTOR 4 POLES +  70736000_Plug Connector IP 68 4 Pole + PE 0.5-1.5 mm ² WP5/M (TEKOX)			
WP5/M 		 25 pcs. 150x120x110 mm	 0,53 Kg
FLEXIBLE CABLE  14-15 mm 7,8 mm 0,5 -1,5 mm ² Cable seals included Ø9,5mm, Ø11,5mm Ø12,5mm	 46,5 ⁺² Ø25,5	 -40°C +85°C Voltage/Current rating 450V / 17,5A	
SOCKET PLUGGABLE CONNECTOR 4 POLES +  70737000_Socket Connector IP 68 4 Pole + PE 0.5-1.5 mm ² WP5/H (TEKOX)			
WP5/H 		 25 pcs. 150x120x110 mm	 0,56 Kg
FLEXIBLE CABLE  14-15 mm 7,8 mm 0,5 -1,5 mm ² Cable seals included Ø9,5mm, Ø11,5mm Ø12,5mm	 50,5 ⁺² Ø25,5	 -40°C +85°C Voltage/Current rating 450V / 17,5A	